



## DVI, DISPLAY PORT, HDMI, VIDEO INTERFACE CONTROLLER FOR TFT PANEL

**Model: SVX-4096-120**

Part number : 41759001X-3 or up

### INSTRUCTIONS

#### CONTENTS

|       |   |
|-------|---|
| Page: | <b>2. Introduction, How to Proceed, Usage Note, Disclaimer</b>                  |
|       | <b>3. System design</b> – Diagram of a suggested system                         |
|       | <b>4. Assembly notes</b> – Important information about system elements          |
|       | <b>6. Connection &amp; Operation</b> – How to use the controller                |
|       | <b>12. Connectors, pinouts &amp; jumpers</b> – Essential connection information |
|       | <b>28. Controller dimensions</b>  |
|       | <b>29. Application notes</b>  |
|       | <b>31. Troubleshooting</b>  |
|       | <b>32. Specifications</b>   |
|       | <b>33. Appendix I</b> – Signal support modes table                              |
|       | <b>37. Appendix II</b> - Network connection                                     |
|       | <b>38. Appendix III</b> – RS-232 control protocols and command set              |
|       | <b>47. Appendix IV</b> - Mapping definition                                     |
|       | <b>49. Appendix V</b> – DV remote control unit work for SVX-4096                |
|       | <b>50. Appendix VI</b> - PIP mix table  |
|       | <b>51. Warranty, Caution &amp; Limitation of Liability, Trademarks</b>          |
|       | <b>52. Contact details</b>  |
|       | <b>53. Revision History</b>   |

**It is essential that these instructions are read and understood before connecting or powering up this controller.**

---

## Introduction

Designed for LCD monitor and other flat panel display applications, the SVX-4096-120 is a feature rich interface controller for :

- TFT (active matrix) LCD panels of 4096x2160 resolutions in 60Hz or 120Hz with V-by-One interface.
- Support true 10 bits panel
- Support HDMI, DVI and Display Port input.

### HOW TO PROCEED

- Ensure you have all parts & that they are correct, refer to:
  - Connection diagram

#### Controller Solution Generator

Full web resource matching controllers & panels with **connection diagrams** for download.  
See at : <http://www.digitalview.com/csg>

- Connector reference (in following section)
- Assembly notes
- Check controller switch & jumper settings (errors may damage the panel)
- Prepare the signal sources
- Connect the parts
- Understand the operation & functions

### IMPORTANT USAGE NOTE

This equipment is for use by developers and integrators, the manufacturer accepts no liability for damage or injury caused by the use of this product. It is the responsibility of the developer, integrators or other user of this product to:


- Ensure that all necessary and appropriate safety measures are taken.
- Obtain suitable regulatory approvals as may be required.
- **Check power settings to all component parts before connection.**

### DISCLAIMER

There is no implied or expressed warranty regarding this material.

## SYSTEM DESIGN

A typical LCD based display system utilizing this controller is likely to comprise the following:



## ASSEMBLY NOTES

This controller is designed for monitor and custom display projects using 4096x2160 resolution with V-by-One interface, eDP interface or LVDS TFT panels. The following provides some guidelines for installation and preparation of a finished display solution.

**Preparation:** Before proceeding it is important to familiarize yourself with the parts making up the system and the various connectors, mounting holes and general layout of the controller. As much as possible connectors have been labeled. Guides to connectors and mounting holes are shown in the following relevant sections.

- 1. LCD Panel:** This controller is designed for typical V-by-One (8 or 16 lanes) panels with panel voltage 3.3V, 5V, 10V, 12V or 18V, External for 10V, 12V and 18V interface. Due to the variation between manufacturers of panels signal timing and other panel characteristics, factory setup and confirmation should be obtained before connecting to a panel. **(NOTE: Check panel power jumper settings before connection)**
- 2. LCD Controller:** Handle the controller with care as static charge may damage electronic components. Make sure correct jumper to match the target LCD panel.
- 3. Panel cable:** In order to provide a clean signal it is recommended that all panel cables (V-by-One signal) supplied by Digital View. Care should be taken when placing the cables to avoid signal interference.
- 4. Inverter/Backlight driver:** This will be required for the backlight of an LCD, some LCD panels have an inverter/backlight driver built in. As LCD panels may have 1 or more backlight tubes and the power requirements for different panel backlights may vary it is important to match the inverter/backlight driver in order to obtain optimum performance. See Application notes page 29 for more information on connection.
- 5. Inverter/backlight cables:** Different inverter/backlight models require different cables and different pin assignment. Make sure correct cable pin out to match the inverter/backlight. Using wrong cable pin out may damage the inverter/backlight.
- 6. Function Controls:** The following section discusses the controls required and the section on connectors provides the detail. The controls are minimal: On/Off, Backlight Brightness (depends on inverter), OSD (5 momentary buttons) analog VR type or (8 momentary buttons) digital type.
- 7. Function controls cable:** The cables to the function switches should be of suitable quality and length so that impedance does not affect performance. Generally lengths up to 1 meter (3 feet) should be acceptable.
- 8. Optional LED (LED1):** The pin direction of the LED1 should be corrected for right color indication. Red color stands for standby. Green colors stands for signal on. The status LED is an optional part only, can be unconnected.
- 9. Optional IR sensor (IR1):** It is an optional part only, can be unconnected if not using IR remote control.
- 10. RS-232 control interface :** Serial control via this interface port.
- 11. External panel power output :** User for specific panel model.
- 12. Panel control signal :** Use for specific panel model.
- 13. SPDIF Audio output :** This port support SPDIF audio output from the HDMI / Display Port audio source inputted.
- 14. Ambient light sensor connection (CN9) :** 3 ways connector provides interface for ambient light sensor connection by using Kit 70220-3.
- 15. Backlight status input :** 2 ways connector provides interface for connection with the specific panel type which support the panel with backlight status monitoring function.
- 16. DVI-I input cable :** Plug the DVI cable to the connector P1 on the controller board.
- 17. HDMI input :** Plug the HDMI cable to the connector P2(HDMI 1.4) / P3(HDMI 1.4) / P4(HDMI 2.0) on the controller board. This port is not supported when CN5/CN16 are connected.
- 18. Alternate HDMI input :** This port gives alternate HDMI (1.4) input support.
- 19. Alternate DVI-I input :** This port gives alternate DVI-I input support.
- 20. Control over network connection :** This is a network device that allow to control RS-232 enable devices over a TCP/IP based Ethernet and the Internet using a web browser. Please refer to Appendix II in details.
- 21. Reserved for Audio adaptor board P/N 416940020-3:** The audio add-on board gives the audio input and output signal connection. It is an optional and reserved part only, can be unconnected if not using audio. It requires an audio cable P/N 426451800-3 to connect SVX-4096-120 (CN14) to the Audio Add-on Board (CN2).  
CAUTION : The Audio Add-on Board P/N 416940020-3 can only operate with 12VDC power input environment.
- 22. Reserved for Audio extend cable :** The audio extend cable P/N 426009700-3 designs for connection between audio add on board P/N 416940020-3 and the controller. It is an optional and reserved part only, can be unconnected if not using audio.

Specifications subject to change without notice

- 23. Additional panel power input :** Provide additional (+10V/+12V/+18V) panel power input for driving high power consumption panels.
- 24. Power Input:** 12V/24VDC is required, this should be a regulated supply. It allows 12V (5A) or 24V (5A) via PP5 power input connector. The power rating is depending on the panel and inverter used. Although the controller provides power regulation for the LCD power this does not relate to the power supplied to the backlight inverter. If an unregulated power supply is provided to an inverter any fluctuations in power may affect operation, performance and lifetime of the inverter and or backlight tubes.
- 25. External panel power input :** Allow to supply external power to the panel separately for max 3.3V (7A) or 5V (7A) or 10V (5A) or 12V (5A) or 18V (3.5A) via PP4 power input connector. Corresponding jumper setting of JA3, JA7, JA8 & JA9 are required for each panel power input by referring to page 16 and page 17.
- **Power output:** Note the controller has an overall 3Amp current limit and the current available from the auxiliary power output will be dependent on the power input and other system requirements.
  - **Power Safety:** Note that although only 12V / 24VDC is required as 'power-in' a backlight inverter for panel backlighting produces significantly higher voltages (the inverter does not connect to the ground plane). We strongly advise appropriate insulation for all circuitry.
  - **EMI:** Shielding will be required for passing certain regulatory emissions tests. Also the choice of external Controller to PC signal cable can affect the result.
  - **Ground:** The various PCB mounting holes are connected to the ground plane.
  - **Servicing:** The board is not user serviceable or repairable. Warranty does not cover user error in connecting up to the controller and is invalidated by unauthorized modification or repairs.
  - **Controller Mounting:** It is recommended that a clearance of at least 10mm is provided above and 5mm below the controller when mounted. Additionally consideration should be given to:
    - Electrical insulation.
    - Grounding.
    - EMI shielding.
    - Cable management. Note: It is important to keep panel signal cables apart from the inverter & backlight cables to prevent signal interference.
    - Heat & Ventilation: Heat generated from other sources, for example the backlight of a very high brightness panel may generate significant heat which could adversely affect the controller.
    - Other issues that may affect safety or performance.
  - **PC Graphics Output:** A few guidelines:
    - Signal quality is very important, if there is noise or instability in the PC graphics output this may result in visible noise on the display.
    - Refer to graphics modes table in specifications section for supported modes.
    - Non-interlaced & interlaced video input is acceptable.

**IMPORTANT: Please read the Application Notes section for more information.**

---

## CONNECTION & OPERATION

**CAUTION:** Never connect or disconnect parts of the display system when the system is powered up as this may cause serious damage.

### CONNECTION

Connection and usage is quite straight forward (it is useful to have the relevant connection diagram available at this time):

1. **LCD panel & Inverter:** Connect the inverter/Backlight driver (if it is not built-in the panel) to the inverter/backlight connector of the LCD panel.
2. **V-by-One interface panels:** The controller board supports V-by-One interface 4K panel. Plug the cable to J7\_OUT for driving 4K 60Hz or 120Hz panel. And make sure the matching panel timings and correct jumper settings by referring to the panel support table and jumper settings table in page 15-18.
3. **Inverter/Backlight driver:** Plug the inverter/backlight cable to CNB1 and CNA1 (if necessary). Plug another end to the connector on the inverter/backlight of panel side.
4. **Function switch & Controller:** Plug the OSD switch mount cable to CNC1 on the controller board and another to the OSD switch mount.
5. **LED & Controller:** Plug in a 3-way with dual color LED to connector LED1 on the controller board.
6. **IR & Controller:** Plug in a 3-way with IR sensor to connector IR1 on the controller board.
7. **Jumpers & Inverter & Panel voltage:** Particularly pay attention to the settings of JA3, JA7, JA8, JA9, JB2 and JB3. JB2 & JB3 are used for inverter control (read inverter specification and information on the jumper table to define the correct settings). JA3, JA7, JA8 & JA9 are used for panel voltage input (read panel specification and information on the jumper table to define the correct settings).
8. **Input signal cable & Controller:** Plug the corresponding signal input to the connector on the controller board.
9. **Power supply & Controller:** Plug the DC 12V/24V power in to the connector PP2 or PP5. You can consider to use DigitalView mating power cable P/N 426013710-3, 1000mm for PP5 connection.
10. **External panel power input :** Plug power cable : P/N 426013710-3 for external panel power input (3.3 (max 7A) / 5V (max. 7A) / 10V (max. 5A) / 12V (max. 5A) / 18V (max. 3.5A)) for PP4 connection..
11. **Power on:** Switch on the controller board and panel by using the OSD switch mount.

General:

- If you are using supplied cables & accessories, ensure they are correct for the model of panel and controller.
- If you are making your own cables & connectors refer carefully to both the panel & backlight specifications and the section in this manual, "Connectors, Pinouts & Jumpers" to ensure the correct pin to pin wiring.

### PC SETTINGS

The controller has been designed to take a very wide range of input signals however to optimize the PC's graphics performance we recommend choosing 60Hz vertical refresh rate – this will not cause screen flicker.


### OPERATION

Once the system has been connected and switched on there are a number of functions available to adjust the display image as summarized in the following sections. The settings chosen will be saved for each mode independently.

### LCD DISPLAY SYSTEM SETTINGS


NOTE: By way of explanation the following refers to a set of sample buttons that may be obtained as an option. In addition to power on/off and connection for backlight brightness the controller provides an On Screen Display of certain functions which are controlled by 5 momentary type buttons (analog VR type) or 8 momentary type buttons (digital type):

| Controls   | Analog VR type   | Digital type           |
|--|------------------|------------------------|
| On/Off – turns controller board power on   | VR toggle switch | On/Off button          |
| Brightness – controls backlight brightness   | Rotary VR        | Brightness +/- buttons |
| Menu<br>• Turns OSD menu On or Off (it will auto time off)   | Menu button      | Menu button            |
| Select up<br>• Moves the selector to the previous level function (up)                                | SEL UP           | SEL UP                 |
| Select down<br>• Moves the selector to the next level function (down)<br>• Confirm the OSD selection | SEL DN           | SEL DN                 |
| +<br>• Increase the OSD parameter values<br>• Moves the selector to next function (forward)          | +                | +                      |
| -<br>• Decrease the OSD parameter values<br>• Moves the selector to previous function (backward)     | -                | -                      |



Analog VR type


**12V / 24VDC power input :**  
Analog 10K VR Type OSD switch mount uses P/N 410680550-3 or up









Digital type

**12V / 24VDC power input :**  
Digital 10K Type OSD switch mount uses P/N 416100520-3 or up

\* Sequence of Input source selection (Press "+" Button to change source, Press "SEL DN" to confirm)



OSD functions

|   |  |
|---|--|
|  <p>Display Mode</p>     | <p>Display Mode:</p>  <p>[Default]</p>   |
|  <p>Display Function</p> | <p>Display Function:</p> <p>1P: Disp Rotate : 0 [Default]<br/>         90<br/>         180<br/>         270</p> <p>2P LR: Input Swap</p> <p>2P TB: Input Swap</p> <p>2P PIP: PIP Position : Top-left<br/>         Top-right<br/>         Bottom-left<br/>         Bottom-right [Default]</p> <p>PIP Transparency : [0 - 10] [Default 0]<br/>         PIP Size : [0 - 10] [Default 10]<br/>         Input Swap</p> <p>H-Flip: OFF [Default]<br/>         ON</p> <p>V-Flip: OFF [Default]<br/>         ON</p> <p>MEMC: OFF [Default]<br/>         ON</p> |
|  <p>Picture</p>        | <p>Picture:</p> <p>Backlight [0-100] [Default 100]<br/>         Brightness [0-100] [Default 50]<br/>         Contrast [0-100] [Default 50]<br/>         Sharpness [0-4] [Default 2]</p>  |
|  <p>VGA Setup</p>      | <p>VGA Setup:</p> <p>Auto Adjust<br/>         H Position [0-100] [Default 50]<br/>         V Position [0-100] [Default 50]<br/>         Clock [0-100] [Default 50]<br/>         Phase [0-100] [Default 0]</p> <p>Color Gain : Set<br/>         Reset</p>   |
|  <p>Color</p>          | <p>Color:</p> <p>Gamma : 1.8<br/>         2.0<br/>         2.2 [Default]<br/>         2.4</p> <p>Temperature: 9300<br/>         7500<br/>         6500 [Default]<br/>         5800<br/>         3200<br/>         sRGB<br/>         User : R [0-255]</p>   |

Specifications subject to change without notice



G [0-255]  
 B [0-255]

Color Effect: Standard [Default]  
 Game  
 Movie  
 Photo  
 Vivid  
 User: R:  
   Hue [0-100]  
   Sat [0-100]  
 Y:  
   Hue [0-100]  
   Sat [0-100]  
 G:  
   Hue [0-100]  
   Sat [0-100]  
 C:  
   Hue [0-100]  
   Sat [0-100]  
 B:  
   Hue [0-100]  
   Sat [0-100]  
 M:  
   Hue [0-100]  
   Sat [0-100]

Hue: [0-100] [Default 50]  
 Saturation [0-100] [Default 50]



Advance:

Aspect Ratio: Full [Default]  
 16:9  
 4:3  
 5:4  
 1:1

Over Scan: ON [Default]  
 OFF




Over Drive: ONOFF: ON [Default]  
 OFF [Default]  
 OD Gain [0-100] [Default 50]



IP 60: OFF [Default]  
 ON  
 SET

Auto Source Seek: OFF  
 ON [Default]

Hot Key: Hot Key 1 (< | >) : Input  
 Backlight  
 Brightness  
 Contrast  
 Sharpness  
 Hue  
 Saturation  
 Aspect Ratio  
 Display Mode  
 Input Swap  
 PIP Size  
 Auto Adjust  
 Volume  
 No Function [Default]

Hot Key: Hot Key 1 (Up | Dn) : Input  
 Backlight  
 Brightness  
 Contrast  
 Sharpness  
 Hue

|  |  |
|--|--|
|  | <p>Saturation<br/>Aspect Ratio<br/>Display Mode<br/>Input Swap<br/>PIP Size<br/>Auto Adjust<br/>Volume<br/>No Function [Default]</p> <p>Power Save: OFF<br/>ON [Default]</p>   |
|  <p>Input</p>   | <p>Input:<br/>(For all display modes: 1P/ 2R LR / 2P TB / 2P PIP / 4P)</p> <p>A0 : VGA<br/>D0 : DP<br/>D1 : HDMI<br/>D2 : HDMI<br/>D3 : HDMI<br/>D4 : DVI</p>  |
|  <p>Audio</p>   | <p>Audio:</p> <p>Volume [0-100] [Default 50]</p> <p>Mute: ON<br/>OFF [Default]</p> <p>Audio Source (1P) : Analog [Default]<br/>Digital (region 1)</p> <p>Audio Source (2P LR) : Analog [Default]<br/>Digital (region 1) - Left<br/>Digital (region 2) - Right</p> <p>Audio Source (2P TB) : Analog [Default]<br/>Digital (region 1) - Top<br/>Digital (region 2) - Bottom</p> <p>Audio Source (2P PIP) : Analog [Default]<br/>Digital (region 1) - Main<br/>Digital (region 2) - Sub</p> <p>Audio Source (4P) : Analog [Default]<br/>Digital (region 1) - Upper left<br/>Digital (region 2) - Lower left<br/>Digital (region 3) - Upper right<br/>Digital (region 4) - Lower right</p> |
|  <p>Other</p> | <p>Other:</p> <p>Reset</p> <p>Menu Time [On, 11-60] [Default 11]</p> <p>OSD H Position [0-100] [Default 50]</p> <p>OSD V Position [0-100] [Default 50]</p> <p>Language</p> <p>Transparency [0-255] [Default 0]</p> <p>Rotate: 0 [Default 0]<br/>90<br/>270</p> <p>Border Width: [0-10] [Default 0]</p> <p>Border Color: R [Default]</p>  |

|   |  |
|---|--|
|   | <b>G<br/>B<br/>W</b>   |
|  | <p><b>Information:</b></p> <div style="border: 1px solid gray; background-color: #e0e0e0; padding: 5px; margin: 10px auto; width: fit-content;"> <p style="margin: 0;">D: HDMI<br/>3840x2160@60.1Hz<br/>H:135.1KHz PCLK: 594.4MHz<br/>HDCP Disabled</p> </div>   |
|  | <p><b>Factory:</b></p> <p><b>Backlight Setup: Invert : OFF [Default]<br/>ON</b></p> <p style="padding-left: 40px;"><b>D/A / PWM : PWM [Default]<br/>D/A</b></p> <p style="padding-left: 40px;"><b>Frequency : [100Hz - 440Hz] [Default 160Hz]</b></p> <p style="padding-left: 40px;"><b>Min. Level : [0% - 50%] [Default 5%]</b></p> <p><b>VBy1 Setup : Pin 15 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 16 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 17 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 18 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 19 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 20 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 21 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 22 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 23 : Low [Default]<br/>High</b></p> <p style="padding-left: 40px;"><b>Pin 24 : Low [Default]<br/>High</b></p> <p><b>EDID Setup : Reset</b></p> |






|        |  |  |
|--------|--|--|
| CNC1   | OSD control                                | Hirose DF13A-12P-1.25H (Mating type : DF13-12S-1.25C)<br>(Matching OSD switch mount cable P/N 426122200-3 (150mm) or<br>426122210-3 (250mm)) |
| CP2    | Reserved                                   | Reserved   |
| IR1    | Infra-red sensor connector                 | JST 3-way, B3B-XH-A (Matching type : XHP-3)  |
| J1     | Ethernet                                   | RJ-45 connector  |
| J5     | Panel power output                         | JS-1147A-08 Top 1.25mm (Matching type : JS-1146-08)  |
| J6     | Display Port (1.2) transmit out connector  | Display Port connector   |
| J7_OUT | V-by-One panel signal output               | JAE FI-RE51S-HF (Matching type : FI-RE51HL)  |
| J8_OUT | V-by-One panel signal output               | JAE FI-RE41S-HF (Matching type : FI-RE41HL)  |
| LED1   | Power LED connector                        | 3-pins header  |
| P1     | DVI-I -- D4 / VGA -- A0                    | DVI-I connector  |
| P2     | HDMI (1.4) -- D3                           | HDMI connector   |
| P3     | HDMI (1.4) -- D2                           | HDMI connector   |
| P4     | HDMI (2.0) -- D1                           | HDMI connector   |
| P5     | Display Port (1.2) -- D0                   | Display Port connector   |
| PP2    | Power input (alternative)                  | DC power Molex 2 pin 0.156" pitch  |
| PP4    | External panel power input                 | Molex 43045-0400 compatible<br>(Matching connector type : Molex 43025-0400 compatible)<br>(Matching power cable : P/N 426013710-3)           |
| PP5    | 12V/24VDC input power                      | Molex 43045-0400 compatible<br>(Matching connector type : Molex 43025-0400 compatible)<br>(Matching power cable : P/N 426013710-3)           |
| S1     | Reset button (for Ethernet function)       | Tact switch button   |
| S2     | Reserved                                   | Tact switch button   |
| S4     | Config Menu button (for Ethernet function) | Tact switch button   |
| SW1    | Panel timing selection                     | 8-way DIP Switch   |






**Summary: Jumpers setting**

| Ref  | Purpose  | Note  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
|------|--|---|------|-------------|----|-----|--------|----|-----|--------|----|-----|--------|----|----|---------------|----|----|---------------|----|----|---------------|----|----|---------------|----|----|---------------|----|----|---------------|----|----|---------------|----|----|---------------|----|----|---------------|----|-----|--------|----|-------|-----------------|----|-------|-------------|--|
| JA3  | Panel power voltage select<br><b>CAUTION:</b> Incorrect setting can damage panel   | See panel voltage setting table 1   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JA7  | Panel power voltage select<br><b>CAUTION:</b> Incorrect setting will cause panel damage  | See panel voltage setting table 1   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JA8  | Panel power voltage select<br><b>CAUTION:</b> Incorrect setting will cause panel damage  | See panel voltage setting table 1   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JA9  | Panel power voltage select<br><b>CAUTION:</b> Incorrect setting will cause panel damage  | See panel voltage setting table 1   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JB1  | Backlight brightness voltage range   | 1-2 = 5V max<br>2-3 = 3.3V max  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JB2  | Backlight inverter on/off control – signal level   | 2-3 = On/Off control signal 'High' = +5V<br>1-2 = On/Off control signal 'High' = +3.3V<br>Open = On/Off control signal 'High' = Open collector<br><b>CAUTION:</b> Incorrect setting can damage inverter.  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JB3  | Backlight inverter on/off control – polarity   | 1-2 = control signal 'high' = Backlight ON<br>2-3 = control signal 'low' = Backlight ON   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JB4  | Reserved for U58 programming   | 1-2 = Normal use (Default)<br>2-3 = Enable U58 programming  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JB5  | Backlight control type selection   | 1-2 = VR/Digital switch mount control<br>3-4 = Analog backlight brightness - voltage range 0~5V<br>5-6 = PWM (Pulse Width Modulation) brightness  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JB7  | Backlight control voltage on CNB1 pin 4<br><br>(Function when JB5 sets 1-2 closed)   | Open = For OSD switch mount control (Default)<br>1-2 = 0V<br>2-3 = 3.3V / 5V controlled by JB1  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JC1  | <p>Panel Specification<br/>(V-by-One's pin assignment)</p> <table border="1"> <thead> <tr> <th>Pin</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr><td>12</td><td>GND</td><td>Ground</td></tr> <tr><td>13</td><td>GND</td><td>Ground</td></tr> <tr><td>14</td><td>GND</td><td>Ground</td></tr> <tr><td>15</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>16</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>17</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>18</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>19</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>20</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>21</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>22</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>23</td><td>NC</td><td>NO CONNECTION</td></tr> <tr><td>24</td><td>GND</td><td>Ground</td></tr> <tr><td>25</td><td>HTPDN</td><td>Hot plug detect</td></tr> <tr><td>26</td><td>LOCKN</td><td>Lock detect</td></tr> </tbody> </table> <p>Legend:<br/> </p> | Pin   | Name | Description | 12 | GND | Ground | 13 | GND | Ground | 14 | GND | Ground | 15 | NC | NO CONNECTION | 16 | NC | NO CONNECTION | 17 | NC | NO CONNECTION | 18 | NC | NO CONNECTION | 19 | NC | NO CONNECTION | 20 | NC | NO CONNECTION | 21 | NC | NO CONNECTION | 22 | NC | NO CONNECTION | 23 | NC | NO CONNECTION | 24 | GND | Ground | 25 | HTPDN | Hot plug detect | 26 | LOCKN | Lock detect | <p>1-2 close = High<br/>2-3 close = Low or GND<br/>Open = NC</p> <p>* The setting of NC (No connection) is subject to the NC's state defined in panel specification.</p> |
| Pin  | Name   | Description   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 12   | GND  | Ground  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 13   | GND  | Ground  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 14   | GND  | Ground  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 15   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 16   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 17   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 18   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 19   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 20   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 21   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 22   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 23   | NC   | NO CONNECTION   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 24   | GND  | Ground  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 25   | HTPDN  | Hot plug detect   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| 26   | LOCKN  | Lock detect   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JC3  | Factory use  | Default open  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JP1  | Factory use  | Default open  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JP2  | V-by-One power output configuration  | 1-2 = All pin 44 ~ pin 51 on J7 have power output<br>Open = Only the upper four pins have power output<br><br>(Refer to power output enabled/disabled on JA15. But not applicable if JA15 is set to OPEN) |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JP6  | Input power control  | Short = External switch control and fix the board ON<br>Open = Switch mount control   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JP7  | RS-232 (CN8) selection   | 1-3, 2-4 = RS-232 for scalar<br>3-5, 4-6 = U58 (IE-2000 Programming)  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JP8  | RS-232 (CN1) selection   | 1-3, 2-4 = RS-232 for IP-60<br>3-5, 4-6 = U58 (IE-2000 Debug)   |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JP11 | Panel output power pin selection on J7_OUT   | See panel output power pin selection table 2  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |
| JP12 | Panel output power pin selection on J7_OUT   | See panel output power pin selection table 2  |      |             |    |     |        |    |     |        |    |     |        |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |    |               |    |     |        |    |       |                 |    |       |             |  |

**Table 1 : Panel voltage setting table (JA3, JA7, JA8 and JA9) :**

| Input voltage via PP2/PP5 | Panel Voltage | JA3        | JA7       | JA8       | JA9  | Jumper on board   |
|---------------------------|---------------|------------|-----------|-----------|------|---|
| 12VDC                     | 3.3V          | 3V3 closed | 1-2 & 3-4 | OPEN      | OPEN |  |
|                           | 5V            | 5V closed  | 1-2 & 3-4 | OPEN      | OPEN |  |
|                           | 12V           | DON'T CARE | OPEN      | 1-2 & 3-4 | OPEN |  |

**CAUTION: Incorrect setting can damage panel & controller**

| Input voltage via PP2/PP5 | Panel Voltage | JA3        | JA7       | JA8  | JA9  | Jumper on board   |
|---------------------------|---------------|------------|-----------|------|------|---|
| 24VDC**                   | 3.3V          | 3V3 closed | 1-2 & 3-4 | OPEN | OPEN |   |
|                           | 5V            | 5V closed  | 1-2 & 3-4 | OPEN | OPEN |  |
|                           | 10V           | 10V closed | 1-2 & 3-4 | OPEN | OPEN |  |
|                           | 12V           | 12V closed | 1-2 & 3-4 | OPEN | OPEN |  |
|                           | 18V           | 18V closed | 1-2 & 3-4 | OPEN | OPEN |  |


**CAUTION: Incorrect setting can damage panel & controller**

**\*\* Ensure that the backlight inverter supports 24V operation prior to connecting a 24VDC input. Because CNA1 pin 1 and CNB1 pin 2 will output 24VDC if input 24VDC via PP5 or PP2.**

| Input voltage via PP4 | Input voltage via PP2 / PP5 | Panel Voltage | JA3        | JA7  | JA8  | JA9       | Jumper on board |
|-----------------------|-----------------------------|---------------|------------|------|------|-----------|-----------------|
| 3.3V                  | 12V / 24VDC                 | 3.3V          | DON'T CARE | OPEN | OPEN | 1-2 & 3-4 |                 |
| 5V                    |                             | 5V            | DON'T CARE | OPEN | OPEN | 1-2 & 3-4 |                 |
| 10V                   |                             | 10V           | DON'T CARE | OPEN | OPEN | 1-2 & 3-4 |                 |
| 12V                   |                             | 12V           | DON'T CARE | OPEN | OPEN | 1-2 & 3-4 |                 |
| 18V                   |                             | 18V           | DON'T CARE | OPEN | OPEN | 1-2 & 3-4 |                 |
| 24V                   |                             | 24V           | DON'T CARE | OPEN | OPEN | 1-2 & 3-4 |                 |

\* Maximum current for 3.3V, 5V = 7A, Maximum current for 10V, 12V = 5A, Maximum current for 18V, 24V = 3.5A

Please pay attention to the jumper settings on JA3, JA7, JA8 & JA9 which are red in color)







**Table 3 : Panel timing selection (SW1)**

| Pos. # | Function                      | Description  |
|--------|-------------------------------|--|
| 1      | Image flip (H)                | OFF : Disable<br>ON : Enable                                     |
| 2      | Image flip (V)                | OFF : Disable<br>ON : Enable                                     |
| 3      | Data mapping select           | OFF : Mapping B<br>ON : Mapping A                                |
| 4      | Lane count                    | OFF : 8-lane (for 60Hz panel)<br>ON : 16-lane (for 120Hz panel)  |
| 5      | Reserved                      | Reserved   |
| 6      | Byte length and color mapping | OFF : 8 bits (Byte 0 ~ Byte 2)<br>ON : 10 bits (Byte 0 ~ Byte 3) |

Tcon mode

| Pos #7 | Pos #8 | Description |
|--------|--------|-------------|
| OFF    | OFF    | 1 division  |
| OFF    | ON     | 2 divisions |
| ON     | OFF    | 4 divisions |
| ON     | ON     | Reserved    |

**Panel support**

| <b>4K 60Hz panel</b> |                    |                         |
|----------------------|--------------------|-------------------------|
| <i>Manufacturer</i>  | <i>Panel model</i> | <i>Panel resolution</i> |
| AU Optronics         | P550QVN01.0        | 3840 x 2160             |
| AU Optronics         | P750QVN01.1        | 3840 x 2160             |
| Innolux              | M280DGJ-L30*       | 3840 x 2160             |
| Innolux              | M315DJJ-K30        | 3840 x 2160             |
| Innolux              | S400DJ1-KS5        | 3840 x 2160             |
| Innolux              | V400DK2-KS5        | 3840 x 2160             |
| Innolux              | V420DK1-KS1        | 3840 x 2160             |
| Innolux              | V500DK2-KS1        | 3840 x 2160             |
| LG                   | LC430EQE-FHM1      | 3840 x 2160             |
| LG                   | LC490EQE-FHM2      | 3840 x 2160             |
| LG                   | LC550EQE-FHM1      | 3840 x 2160             |
| LG                   | LD550EGE-FHM1      | 3840 x 2160             |
| LG                   | LD750DGN-FKH1      | 3840 x 2160             |

| <b>4K 120Hz panel</b> |                    |                         |
|-----------------------|--------------------|-------------------------|
| <i>Manufacturer</i>   | <i>Panel model</i> | <i>Panel resolution</i> |
| AU Optronics          | P650QVN01.0*       | 3840 x 2160             |
| AU Optronics          | P750QVN01.0        | 3840 x 2160             |
| Innolux               | V400DK2-KS5        | 3840 x 2160             |
| Innolux               | V500DK1-KS2        | 3840 x 2160             |
| Innolux               | V500DK1-KS5        | 3840 x 2160             |
| Innolux               | V850DK1-KD1        | 3840 x 2160             |
| LG                    | LC550EQD-FGF2      | 3840 x 2160             |
| LG                    | LD750EQF-FJM1      | 3840 x 2160             |
| LG                    | LD840EQD-SEM1      | 3840 x 2160             |
| LG                    | LD860EQD-FJM1      | 3840 x 2160             |
| LG                    | LD980DQD-FGM1      | 3840 x 2160             |
| LG                    | ND840EQD-SADX1     | 3840 x 2160             |

Remark :

1. The panel model marked with (\*) means the model has been verified by DigitalView.
2. The panel model without marked with (\*) means the model has not been tested and verified but have a suggested connection diagram provide.

**CN1 – RS-232 serial control (2nd): JST B6B-XH-A (Matching type : XHP-6)**

| PIN | SYMBOL | DESCRIPTION    |
|-----|--------|----------------|
| 1   | NC     | No connection  |
| 2   | NC     | No connection  |
| 3   | VCC    | +5V            |
| 4   | TXD    | RS-232 Tx data |
| 5   | GND    | Ground         |
| 6   | RXD    | RS-232 Rx data |

**CN2 – Alternate DVI connector: JST BM20B-SRDS (Matching type : SHDR-20V-S-B)**

| PIN | SYMBOL  | DESCRIPTION                         |
|-----|---------|-------------------------------------|
| 1   | GND     | Digital Ground                      |
| 2   | GND     | Digital Ground                      |
| 3   | RXC     | TMDS Clock+                         |
| 4   | /RXC    | TMDS Clock-                         |
| 5   | RX0     | TMDS Data 0+                        |
| 6   | /RX0    | TMDS Data 0-                        |
| 7   | RX1     | TMDS Data 1+                        |
| 8   | /RX1    | TMDS Data 1-                        |
| 9   | RX2     | TMDS Data 2+                        |
| 10  | /RX2    | TMDS Data 2-                        |
| 11  | GND     | Ground (+5, Analog H/V Sync)        |
| 12  | GND     | Digital Ground                      |
| 13  | EXT_SCL | Reserved                            |
| 14  | EXT_SDA | Reserved                            |
| 15  | DDC_5V  | +5V power supply for DDC (optional) |
| 16  | HPD     | Hot plug detect                     |
| 17  | DDC_CLK | DDC Clock                           |
| 18  | DDC_DAT | DDC Data                            |
| 19  | NC      | No connection                       |
| 20  | VCC     | +5V                                 |

**CN3 – Temperature sensor connector : JST B3B-XH-A (Matching type : XHP-3)**

| PIN | SYMBOL        | DESCRIPTION              |
|-----|---------------|--------------------------|
| 1   | GND           | Ground                   |
| 2   | VDD           | +3.3V                    |
| 3   | EX_TMP_SENSOR | Temperature sensor input |

**CN5 - Alternate HDMI connector : JST BM20B-SRDS (Matching type : SHDR-20V-S-B)**

| PIN | SYMBOL  | DESCRIPTION                         |
|-----|---------|-------------------------------------|
| 1   | GND     | Ground                              |
| 2   | GND     | Ground                              |
| 3   | RXC+    | TMDS Data C+                        |
| 4   | RXC-    | TMDS Data C-                        |
| 5   | RX0+    | TMDS Data 0+                        |
| 6   | RX0-    | TMDS Data 0-                        |
| 7   | RX1+    | TMDS Data 1+                        |
| 8   | RX1-    | TMDS Data 1-                        |
| 9   | RX2+    | TMDS Data 2+                        |
| 10  | RX2-    | TMDS Data 2-                        |
| 11  | GND     | Ground                              |
| 12  | GND     | Ground                              |
| 13  | EXT_SCL | Reserved                            |
| 14  | EXT_SDA | Reserved                            |
| 15  | DDC_5V  | +5V power supply for DDC (optional) |
| 16  | HPD     | Hot plug detection                  |
| 17  | DDC_SCL | DDC serial clock                    |
| 18  | DDC_SDA | DDC Data                            |
| 19  | NC      | No connection                       |
| 20  | VCC     | +5V                                 |

**CN6 – Light sensor connector : DF13 2-ways (Matching type : DF13-2S-1.25C)**

| PIN | SYMBOL | DESCRIPTION        |
|-----|--------|--------------------|
| 1   | SENSOR | Light sensor input |
| 2   | VDD    | +3.3V              |

**CN7 - Audio board connector : 2x5 right angled header (Matching audio add-on board P/N 416940020-3 & Audio extend cable P/N 426009700-3)**

| PIN | SYMBOL    | DESCRIPTION                         |
|-----|-----------|-------------------------------------|
| 1   | VCC       | Audio board logic power supply, +5V |
| 2   | VOLSEL0   | Reserved                            |
| 3   | VOLSEL1   | Reversed                            |
| 4   | TUNAUSEL  | Reserved                            |
| 5   | CLK/CNT   | Reserved                            |
| 6   | GND       | Ground                              |
| 7   | +12V/+24V | Audio board power supply, +12V/+24V |
| 8   | NC        | No connection                       |
| 9   | NC        | No connection                       |
| 10  | GND       | Ground                              |

**CN8 – RS-232 serial control: JST B6B-XH-A (Matching type : XHP-6)**

| PIN | SYMBOL  | DESCRIPTION    |
|-----|---------|----------------|
| 1   | EXT_SCL | Reserved       |
| 2   | EXT_SDA | Reserved       |
| 3   | VCC     | +5V            |
| 4   | TXD     | RS-232 Tx data |
| 5   | GND     | Ground         |
| 6   | RXD     | RS-232 Rx data |

**CN9 – Ambient light sensor connector : JST B3B-PH-K (Matching type : PHR-3)**

| PIN | SYMBOL | DESCRIPTION                    |
|-----|--------|--------------------------------|
| 1   | GND    | Ground                         |
| 2   | VCC_5V | VCC 5V                         |
| 3   | ALSF   | Ambient light sensing feedback |

**CN10 - Fan and backlight power monitoring connector : Hirose DF13-9P-1.25 DSA (Matching type : DF13-9S-1.25C)**

| PIN | SYMBOL   | DESCRIPTION            |
|-----|----------|------------------------|
| 1   | GND      | Ground                 |
| 2   | TACH1_IN | Tachometer IN of Fan 1 |
| 3   | GND      | Ground                 |
| 4   | TACH2_IN | Tachometer IN of Fan 2 |
| 5   | GND      | Ground                 |
| 6   | PS_V1_IN | Power sense input 1    |
| 7   | GND      | Ground                 |
| 8   | PS_V2_IN | Power sense input 2    |
| 9   | AUX      | Reserved               |

**CN11 – SPDIF audio output connector : JST B2B-ZR (Matching type : ZHR-2)**

| PIN | SYMBOL | DESCRIPTION                |
|-----|--------|----------------------------|
| 1   | SPDIF  | SPDIF Digital audio output |
| 2   | GND    | Ground                     |

**CN12 – Reserved**

**CN13 - Audio line in: JST B4B-ZR (Matching type : ZHR-4)**

| PIN | SYMBOL    | DESCRIPTION     |
|-----|-----------|-----------------|
| 1   | GND       | Ground          |
| 2   | LINE_IN_L | Line in (Left)  |
| 3   | GND       | Ground          |
| 4   | LINE_IN_R | Line in (Right) |

**CN14 - Audio line out: JST B4B-ZR (Matching type : ZHR-4)**

| PIN | SYMBOL      | DESCRIPTION       |
|-----|-------------|-------------------|
| 1   | GND         | Ground            |
| 2   | AUDIO_OUT_L | Audio out (Left)  |
| 3   | GND         | Ground            |
| 4   | AUDIO_OUT_R | Audio out (Right) |

**CN16 - Alternate HDMI connector : JST BM20B-SRDS (Matching type : SHDR-20V-S-B)**

| PIN | SYMBOL | DESCRIPTION  |
|-----|--------|--------------|
| 1   | GND    | Ground       |
| 2   | GND    | Ground       |
| 3   | RXC+   | TMDS Data C+ |
| 4   | RXC-   | TMDS Data C- |
| 5   | RX0+   | TMDS Data 0+ |
| 6   | RX0-   | TMDS Data 0- |

Specifications subject to change without notice

|    |         |                                       |
|----|---------|---------------------------------------|
| 7  | RX1+    | TMDS Data 1+                          |
| 8  | RX1-    | TMDS Data 1-                          |
| 9  | RX2+    | TMDS Data 2+                          |
| 10 | RX2-    | TMDS Data 2-                          |
| 11 | GND     | Ground                                |
| 12 | GND     | Ground                                |
| 13 | EXT_SCL | Reserved                              |
| 14 | EXT_SDA | Reserved                              |
| 15 | DDC_5V  | +5V power supply for DDC (optional)   |
| 16 | NC      | No connection                         |
| 17 | DDC_SCL | DDC serial clock                      |
| 18 | DDC_SDA | DDC Data                              |
| 19 | CEC     | Consumer Electronics Control(CEC) pin |
| 20 | VCC     | +5V                                   |

**CN19 – Additional panel power output : JST B10B-PH-K (Matching type : PHR-10)**

| PIN | SYMBOL     | DESCRIPTION  |
|-----|------------|--|
| 1   | PVLCD_High | Panel power supply (+10V / 12V / 18V) (selected by JA3, JA5 & JA6) |
| 2   | PVLCD_High | Panel power supply (+10V / 12V / 18V) (selected by JA3, JA5 & JA6) |
| 3   | PVLCD_High | Panel power supply (+10V / 12V / 18V) (selected by JA3, JA5 & JA6) |
| 4   | PVLCD_High | Panel power supply (+10V / 12V / 18V) (selected by JA3, JA5 & JA6) |
| 5   | PVLCD_High | Panel power supply (+10V / 12V / 18V) (selected by JA3, JA5 & JA6) |
| 6   | GND        | Ground   |
| 7   | GND        | Ground   |
| 8   | GND        | Ground   |
| 9   | GND        | Ground   |
| 10  | GND        | Ground   |

**CNA1 - Auxiliary power output: JST B4B-XH-A (Matching type : XHP-4)**

| PIN | SYMBOL        | DESCRIPTION       |
|-----|---------------|-------------------|
| 1   | AUX 12V / 24V | +12V / +24V DC    |
| 2   | GND           | Ground            |
| 3   | GND           | Ground            |
| 4   | AUX 5V        | +5V DC, 500mA max |

**CNB1 – Backlight inverter connector: JST B5B-XH-A (Matching type : XHP-5)**

| PIN | SYMBOL  | DESCRIPTION                             |
|-----|---------|---|
| 1   | GND     | Ground                                  |
| 2   | VBKL    | +12V / +24V DC, backlight power supply  |
| 3   | BLCTRL  | On/Off control (enable) – see JB2 & JB3 |
| 4   | BVR_WIP | Brightness VR – WIP                     |
| 5   | BVR_A   | Brightness VR A                         |

**CNB2 – Backlight status input inverter connector: JST B2B-XH-A (Matching type : XHP-2)**

| PIN | SYMBOL    | DESCRIPTION                      |
|-----|-----------|----------------------------------|
| 1   | BL_STATUS | Backlight status (Normal = High) |
| 2   | GND       | Ground                           |

**CNC1 – OSD switch mount control, Hirose DF13A-12P-1.25H (Mating type : DF13-12S-1.25C)**

| PIN | SYMBOL  | DESCRIPTION   |
|-----|---------|---|
| 1   | PSWIN   | Power button A  |
| 2   | SW_ON   | Power button B  |
| 3   | BVR_A   | Backlight Brightness VR pin A                               |
| 4   | BVR_WIP | Backlight Brightness R pin WIP                              |
| 5   | BVR_B   | Backlight Brightness VR pin B (470 ohm resistor to +5V Vcc) |
| 6   | GND     | Ground  |
| 7   | MENU    | OSD menu  |
| 8   | -/LEFT  | OSD -/Left  |
| 9   | +/RIGHT | OSD +/Right   |
| 10  | SEL_DN  | OSD Select down   |
| 11  | SEL_UP  | OSD Select up   |
| 12  | NC      | No connection   |

The VR for brightness depends on the inverter. The main power load for On/Off is handled by a relay on the controller.

**CP2 - Reserved**

**IR1 – Infra-Red sensor connector: JST B3B-XH-A (Matching type : XHP-3)**

| PIN | SYMBOL | DESCRIPTION |
|-----|--------|-------------|
| 1   | GND    | Ground      |
| 2   | VCC    | +3.3V       |

|   |         |         |
|---|---------|---------|
| 3 | IR Data | IR data |
|---|---------|---------|

**J1 – Ethernet connector: RJ-45 connector**

| PIN | SYMBOL | DESCRIPTION     |
|-----|--------|-----------------|
| 1   | TX+    | Transmit data + |
| 2   | TX-    | Transmit data - |
| 3   | RX+    | Receive data +  |
| 4   | CMT1   | Network use     |
| 5   | CMT1   | Network use     |
| 6   | RX-    | Receive data -  |
| 7   | CMT3   | Network use     |
| 8   | CMT3   | Network use     |

**J5 – Panel power output connector: JS-1147A-08 Top 1.25mm (Matching type : JS-1146-08)**

| PIN | SYMBOL              | DESCRIPTION                           |
|-----|---------------------|---------------------------------------|
| 1   | PVLCD_Low (3,3V/5V) | Panel power supply (3,3V/5V)          |
| 2   | PVLCD_Low (3,3V/5V) | Panel power supply (3,3V/5V)          |
| 3   | GND                 | Ground                                |
| 4   | GND                 | Ground                                |
| 5   | GND                 | Ground                                |
| 6   | PVLCD_High          | Panel power supply (+10V / 12V / 18V) |
| 7   | PVLCD_High          | Panel power supply (+10V / 12V / 18V) |
| 8   | PVLCD_High          | Panel power supply (+10V / 12V / 18V) |

**J6 – Display Port (1.2) connector (transmit out)**

| PIN | SYMBOL        | DESCRIPTION                       |
|-----|---------------|-----------------------------------|
| 1   | ML_Lane 0 (p) | Lane 0 (positive)                 |
| 2   | GND           | Ground                            |
| 3   | ML_Lane 0 (n) | Lane 0 (negative)                 |
| 4   | ML_Lane 1 (p) | Lane 1 (positive)                 |
| 5   | GND           | Ground                            |
| 6   | ML_Lane 1 (n) | Lane 1 (negative)                 |
| 7   | ML_Lane 2 (p) | Lane 2 (positive)                 |
| 8   | GND           | Ground                            |
| 9   | ML_Lane 2 (n) | Lane 2 (negative)                 |
| 10  | ML_Lane 3 (p) | Lane 3 (positive)                 |
| 11  | GND           | Ground                            |
| 12  | ML_Lane 3 (n) | Lane 3 (negative)                 |
| 13  | CONFIG1       | connected to Ground               |
| 14  | CONFIG2       | connected to Ground               |
| 15  | AUX CH (p)    | Auxiliary Channel (positive)      |
| 16  | GND           | Ground                            |
| 17  | AUX CH (n)    | Auxiliary Channel (negative)      |
| 18  | Hot Plug      | Hot Plug Detect                   |
| 19  | GND           | Ground                            |
| 20  | DP_PWR        | Power for connector (3.3V 500 mA) |

**J7\_OUT – V-by-One panel signal output connector: JAE FI-RE51S-HF (Matching type : JAE FI-RE51HL)**

| PIN     | SYMBOL   | DESCRIPTION             |
|---------|----------|-------------------------|
| 1 (51)  | GND      | Ground                  |
| 2 (50)  | VB1_TX7P | V-by-One HS Data Lane 7 |
| 3 (49)  | VB1_TX7N | V-by-One HS Data Lane 7 |
| 4 (48)  | GND      | Ground                  |
| 5 (47)  | VB1_TX6P | V-by-One HS Data Lane 6 |
| 6 (46)  | VB1_TX6N | V-by-One HS Data Lane 6 |
| 7 (45)  | GND      | Ground                  |
| 8 (44)  | VB1_TX5P | V-by-One HS Data Lane 5 |
| 9 (43)  | VB1_TX5N | V-by-One HS Data Lane 5 |
| 10 (42) | GND      | Ground                  |
| 11 (41) | VB1_TX4P | V-by-One HS Data Lane 4 |
| 12 (40) | VB1_TX4N | V-by-One HS Data Lane 4 |
| 13 (39) | GND      | Ground                  |
| 14 (38) | VB1_TX3P | V-by-One HS Data Lane 3 |
| 15 (37) | VB1_TX3N | V-by-One HS Data Lane 3 |
| 16 (36) | GND      | Ground                  |
| 17 (35) | VB1_TX2P | V-by-One HS Data Lane 2 |
| 18 (34) | VB1_TX2N | V-by-One HS Data Lane 2 |
| 19 (33) | GND      | Ground                  |
| 20 (32) | VB1_TX1P | V-by-One HS Data Lane 1 |
| 21 (31) | VB1_TX1N | V-by-One HS Data Lane 1 |
| 22 (30) | GND      | Ground                  |
| 23 (29) | VB1_TX0P | V-by-One HS Data Lane 0 |

Specifications subject to change without notice

|    |      |                 |   |
|----|------|-----------------|---|
| 24 | (28) | VB1_TX0N        | V-by-One HS Data Lane 0                             |
| 25 | (27) | GND             | Ground  |
| 26 | (26) | LOCKN           | V-by-One LOCK                                       |
| 27 | (25) | HTPDN           | V-by-One HTPDN                                      |
| 28 | (24) | OP10            | High/Low state control                              |
| 29 | (23) | OP9             | High/Low state control                              |
| 30 | (22) | OP8             | High/Low state control                              |
| 31 | (21) | OP7             | High/Low state control                              |
| 32 | (20) | OP6             | High/Low state control                              |
| 33 | (19) | OP5 / PANEL_SCL | High/Low state control / Panel I <sup>2</sup> C SCL |
| 34 | (18) | OP4 / PANEL_SDA | High/Low state control / Panel I <sup>2</sup> C SDA |
| 35 | (17) | OP3             | High/Low state control                              |
| 36 | (16) | OP2             | High/Low state control                              |
| 37 | (15) | OP1             | High/Low state control                              |
| 38 | (14) | GND             | Ground  |
| 39 | (13) | GND             | Ground  |
| 40 | (12) | GND             | Ground  |
| 41 | (11) | GND             | Ground  |
| 42 | (10) | GND             | Ground  |
| 43 | (9)  | NC              | No Connection                                       |
| 44 | (8)  | PVLCD_High      | Panel power supply (selected by JA15 & JP2)         |
| 45 | (7)  | PVLCD_High      | Panel power supply (selected by JA15 & JP2)         |
| 46 | (6)  | PVLCD_High      | Panel power supply (selected by JA15 & JP2)         |
| 47 | (5)  | PVLCD_High      | Panel power supply (selected by JA15 & JP2)         |
| 48 | (4)  | PVLCD_High      | Panel power supply (selected by JA15 & JP2)         |
| 49 | (3)  | PVLCD_High      | Panel power supply (selected by JA15 & JP2)         |
| 50 | (2)  | PVLCD_High      | Panel power supply (selected by JA15 & JP2)         |
| 51 | (1)  | PVLCD_High      | Panel power supply (selected by JA15 & JP2)         |

(1) - (51): Pin# read on panel side.

**J8\_OUT – V-by-One panel signal output connector: JAE FI-RE41S-HF (Matching type : JAE FI-RE41HL)**

| PIN | SYMBOL    | DESCRIPTION      |
|-----|-----------|------------------|
| 1   | NC        | No connection    |
| 2   | NC        | No connection    |
| 3   | NC        | No connection    |
| 4   | NC        | No connection    |
| 5   | NC        | No connection    |
| 6   | NC        | No connection    |
| 7   | NC        | No connection    |
| 8   | NC        | No connection    |
| 9   | NC        | No connection    |
| 10  | NC        | No connection    |
| 11  | NC        | No connection    |
| 12  | NC        | No connection    |
| 13  | NC        | No connection    |
| 14  | NC        | No connection    |
| 15  | NC        | No connection    |
| 16  | NC        | No connection    |
| 17  | GND       | Ground           |
| 18  | VB1_TX15P | V-By-One Lane 15 |
| 19  | VB1_TX15N | V-By-One Lane 15 |
| 20  | GND       | Ground           |
| 21  | VB1_TX14P | V-By-One Lane 14 |
| 22  | VB1_TX14N | V-By-One Lane 14 |
| 23  | GND       | Ground           |
| 24  | VB1_TX13P | V-By-One Lane 13 |
| 25  | VB1_TX13N | V-By-One Lane 13 |
| 26  | GND       | Ground           |
| 27  | VB1_TX12P | V-By-One Lane 12 |
| 28  | VB1_TX12N | V-By-One Lane 12 |
| 29  | GND       | Ground           |
| 30  | VB1_TX11P | V-By-One Lane 11 |
| 31  | VB1_TX11N | V-By-One Lane 11 |
| 32  | GND       | Ground           |
| 33  | VB1_TX10P | V-By-One Lane 10 |
| 34  | VB1_TX10N | V-By-One Lane 10 |
| 35  | GND       | Ground           |
| 36  | VB1_TX9P  | V-By-One Lane 9  |
| 37  | VB1_TX9N  | V-By-One Lane 9  |
| 38  | GND       | Ground           |
| 39  | VB1_TX8P  | V-By-One Lane 8  |
| 40  | VB1_TX8N  | V-By-One Lane 8  |
| 41  | GND       | Ground           |

Specifications subject to change without notice



**LED1 – Status LED connector: 3-pin header**

| PIN | DESCRIPTION              |
|-----|--------------------------|
| 1   | Green LED pin (anode)    |
| 2   | LED pin common (cathode) |
| 3   | Red LED pin (anode)      |

**P1 – DVI-I (Dual link) in**

| PIN | SYMBOL  | DESCRIPTION                         |
|-----|---------|-------------------------------------|
| 1   | /RX2    | TMDS Data 2-                        |
| 2   | RX2     | TMDS Data 2+                        |
| 3   | GND     | Digital Ground                      |
| 4   | /Rx4    | TMDS Data 4-                        |
| 5   | Rx4     | TMDS Data 4+                        |
| 6   | DDC_CLK | DDC Clock                           |
| 7   | DDC_DAT | DDC Data                            |
| 8   | VS_IN   | Analog Vertical Sync                |
| 9   | /RX1    | TMDS Data 1-                        |
| 10  | RX1     | TMDS Data 1+                        |
| 11  | GND     | Digital Ground                      |
| 12  | /Rx3    | TMDS Data 3-                        |
| 13  | Rx3     | TMDS Data 3+                        |
| 14  | DDC_5V  | +5V power supply for DDC (optional) |
| 15  | GND     | Ground                              |
| 16  | HPD     | Hot Plug Detect                     |
| 17  | /RX0    | TMDS Data 0-                        |
| 18  | RX0     | TMDS Data 0+                        |
| 19  | GND     | Digital Ground                      |
| 20  | /Rx5    | TMDS Data 5-                        |
| 21  | Rx5     | TMDS Data 5+                        |
| 22  | GND     | Digital Ground                      |
| 23  | RXC     | TMDS Clock+                         |
| 24  | /RXC    | TMDS Clock-                         |
| C1  | RIN     | Analog Red                          |
| C2  | GIN     | Analog Green                        |
| C3  | BIN     | Analog Blue                         |
| C4  | HS_IN   | Analog horizontal sync              |
| C5  | GND     | Ground                              |
| C6  | NC      | No connection                       |

**P2 – HDMI (1.4) connector**

| PIN | SYMBOL | DESCRIPTION                                     |
|-----|--------|---|
| 1   | DATA2+ | TMDS Data2+                                     |
| 2   | DATA2S | TMDS Data2 Shield                               |
| 3   | DATA2- | TMDS Data2-                                     |
| 4   | DATA1+ | TMDS Data1+                                     |
| 5   | DATA1S | TMDS Data1 Shield                               |
| 6   | DATA1- | TMDS Data1-                                     |
| 7   | DATA0+ | TMDS Data0+                                     |
| 8   | DATA0S | TMDS Data0 Shield                               |
| 9   | DATA0- | TMDS Data0-                                     |
| 10  | CLK+   | TMDS Clock+                                     |
| 11  | CLK@   | TMDS Clock Shield                               |
| 12  | CLK-   | TMDS Clock-                                     |
| 13  | NC     | No connection                                   |
| 14  | NC     | No connection                                   |
| 15  | SCL    | SCL (I <sup>2</sup> C Serial Clock for DDC)     |
| 16  | SDA    | SDA (I <sup>2</sup> C Serial Data Line for DDC) |
| 17  | GND    | Ground  |
| 18  | +5V    | +5 V Power (max 50 mA)                          |
| 19  | HPDET  | Hot Plug Detect                                 |

**P3 – HDMI (1.4) connector**

| PIN | SYMBOL | DESCRIPTION       |
|-----|--------|-------------------|
| 1   | DATA2+ | TMDS Data2+       |
| 2   | DATA2S | TMDS Data2 Shield |
| 3   | DATA2- | TMDS Data2-       |
| 4   | DATA1+ | TMDS Data1+       |
| 5   | DATA1S | TMDS Data1 Shield |
| 6   | DATA1- | TMDS Data1-       |
| 7   | DATA0+ | TMDS Data0+       |

Specifications subject to change without notice

|    |        |   |
|----|--------|---|
| 8  | DATA0S | TMDS Data0 Shield                               |
| 9  | DATA0- | TMDS Data0-                                     |
| 10 | CLK+   | TMDS Clock+                                     |
| 11 | CLK@   | TMDS Clock Shield                               |
| 12 | CLK-   | TMDS Clock-                                     |
| 13 | NC     | No connection                                   |
| 14 | NC     | No connection                                   |
| 15 | SCL    | SCL (I <sup>2</sup> C Serial Clock for DDC)     |
| 16 | SDA    | SDA (I <sup>2</sup> C Serial Data Line for DDC) |
| 17 | GND    | Ground  |
| 18 | +5V    | +5 V Power (max 50 mA)                          |
| 19 | HPDET  | Hot Plug Detect                                 |

**P4 – HDMI (2.0) connector**

| PIN | SYMBOL | DESCRIPTION                                     |
|-----|--------|---|
| 1   | DATA2+ | TMDS Data2+                                     |
| 2   | DATA2S | TMDS Data2 Shield                               |
| 3   | DATA2- | TMDS Data2-                                     |
| 4   | DATA1+ | TMDS Data1+                                     |
| 5   | DATA1S | TMDS Data1 Shield                               |
| 6   | DATA1- | TMDS Data1-                                     |
| 7   | DATA0+ | TMDS Data0+                                     |
| 8   | DATA0S | TMDS Data0 Shield                               |
| 9   | DATA0- | TMDS Data0-                                     |
| 10  | CLK+   | TMDS Clock+                                     |
| 11  | CLK@   | TMDS Clock Shield                               |
| 12  | CLK-   | TMDS Clock-                                     |
| 13  | NC     | No connection                                   |
| 14  | NC     | No connection                                   |
| 15  | SCL    | SCL (I <sup>2</sup> C Serial Clock for DDC)     |
| 16  | SDA    | SDA (I <sup>2</sup> C Serial Data Line for DDC) |
| 17  | GND    | Ground  |
| 18  | +5V    | +5 V Power (max 50 mA)                          |
| 19  | HPDET  | Hot Plug Detect                                 |

**P5 – Display Port (1.2) connector**

| PIN | SYMBOL        | DESCRIPTION                       |
|-----|---------------|-----------------------------------|
| 1   | ML_Lane 0 (p) | Lane 0 (positive)                 |
| 2   | GND           | Ground                            |
| 3   | ML_Lane 0 (n) | Lane 0 (negative)                 |
| 4   | ML_Lane 1 (p) | Lane 1 (positive)                 |
| 5   | GND           | Ground                            |
| 6   | ML_Lane 1 (n) | Lane 1 (negative)                 |
| 7   | ML_Lane 2 (p) | Lane 2 (positive)                 |
| 8   | GND           | Ground                            |
| 9   | ML_Lane 2 (n) | Lane 2 (negative)                 |
| 10  | ML_Lane 3 (p) | Lane 3 (positive)                 |
| 11  | GND           | Ground                            |
| 12  | ML_Lane 3 (n) | Lane 3 (negative)                 |
| 13  | CONFIG1       | connected to Ground               |
| 14  | CONFIG2       | connected to Ground               |
| 15  | AUX CH (p)    | Auxiliary Channel (positive)      |
| 16  | GND           | Ground                            |
| 17  | AUX CH (n)    | Auxiliary Channel (negative)      |
| 18  | Hot Plug      | Hot Plug Detect                   |
| 19  | GND           | Ground                            |
| 20  | DP_PWR        | Power for connector (3.3V 500 mA) |

**PP2 – Alternate 12V/24VDC input power: Molex 2 pin 0.156" pitch**

| PIN | DESCRIPTION       |
|-----|-------------------|
| 1   | +12VDC / 24VDC in |
| 2   | Ground            |


**PP4 – External panel power input: Molex 43045-0400 or compatible (Matching type : Molex 43025-0400 or compatible)**

| PIN | DESCRIPTION          |
|-----|----------------------|
| 1   | External panel power |
| 2   | Ground               |
| 3   | External panel power |
| 4   | Ground               |

**PP5 – 12V/24VDC input power: Molex 43045-0400 or compatible (Matching type : Molex 43025-0400 or compatible)**

| PIN | DESCRIPTION       |
|-----|-------------------|
| 1   | +12VDC / 24VDC in |
| 2   | Ground            |
| 3   | +12VDC / 24VDC in |
| 4   | Ground            |

## CONTROLLER DIMENSIONS



**Ready-made 3D Pro-E (SLDPRT) drawing files** - Save time and effort for your system volumetric analysis design. Includes jpg file previews. Please go to download at <http://www.digitalview.com/products/svx-4096-120-lcd-controller>

The maximum thickness of the controller is 18.93mm with or without video add-on board (measured from bottom of PCB to top of components, including any underside components & leads). We recommend clearances of:

- 5mm from bottom of PCB - if mounting on a metal plate we also recommend a layer of suitable insulation material is added to the mounting plate surface.
- 10mm above the components
- 3-5mm around the edges

Any of the holes shown above can be used for mounting the PCB, they are 3.2mm in diameter.

**CAUTION: Ensure adequate insulation is provided for all areas of the PCB with special attention to high voltage parts such as the inverter.**

## APPLICATION NOTES

### USING THE CONTROLLER WITHOUT BUTTONS ATTACHED

This is very straightforward:

- Firstly setup the controller/display system with the buttons. With controls attached and display system active make any settings for color, tint and image position as required then switch everything off.
- Remove the control switches, the 12-way (CNC1) cable.
- Use a jumper or similar to connect pins 1 & 2 on JP6, this will fix the board On.
- Refer to inverter specifications for details as to fixing brightness to a desired level, this may require a resistor, an open circuit or closed circuit depending on inverter.

**Summary:** On CNC1 the only pins that are used are for On/Off and Brightness (if controller mounted inverter is used). On CNC1 the pins are for momentary type buttons so it doesn't matter that no buttons are attached.

### INVERTER CONNECTION

There are potentially 3 issues to consider with inverter connection:

- Power
- Enable
- Brightness

Please read the following sections for a guide to these issues.

**Inverter Power:** As per the table for CNB1 pin 1 is ground and pin 2 provides 12V/24V DC. This should be matched with the inverter specification: see table.

#### CNB1

| PIN | DESCRIPTION |
|-----|-------------|
| 1   | Ground      |
| 2   | +12V/+24VDC |

Remark: For higher power inverter, more current (for 12V/24V) can be taken from CNA1 pin 1.

**Enable:** This is a pin provided on some inverters for On/Off function and is used by this panel controller for VESA DPMS compliance. If the inverter does not have an enable pin or the enable pin is not used then DPMS will not be operational. Pin 3 should be matched to the inverters specification for the 'enable' or 'disable' pin.

#### CNB1

| PIN | DESCRIPTION |
|-----|-------------|
| 3   | Enable      |

Further, jumpers JB2 & JB3 should be set to match the inverters specification for the enable pin power and High or Low setting: see table.

| Ref | Purpose                 | Note  |
|-----|-------------------------|---|
| JB2 | Inverter enable voltage | 1-2 H = 3.3V, 2-3 H = 5V, OPEN H = open collector |
| JB3 | Inverter control        | 1-2 H = On, 2-3 L = On                            |

**Brightness:** There are various methods for brightness control and it is important to consider the specifications for the inverter to be used. Generally the situation is:

- Brightness can control by using a resistor or VR (Variable Resistor).
- Brightness controlled by adding a circuit such as PWM (Pulse Width Modulation).
- No adjustment of brightness is possible.

CNB1 pins 4 & 5 are available for connecting to an inverter or circuit where VR control is supported.

#### CNB1


| PIN | DESCRIPTION |
|-----|-------------|
| 4   | VR WIP      |
| 5   | VR A        |

This can then be matched with function controls connected to CNC1 pins 4 & 3 or 5: see table.

#### CNC1

| PIN | DESCRIPTION |
|-----|-------------|
| 3   | VR A        |
| 4   | VR WIP      |
| 5   | VR B        |

**Design Guideline for making VR circuitry :**



**Signal description / Notes :**

- 1) R1 : 470ohm on board
- 2) RPOT is an external potentiometer (in-line dip style) that can be plugged directly into CNC1 pins 3,4,5. RPOT must be supplied / installed by user.
- 3) BVR\_B : Voltage tapped from “top” of potentiometer, the node of R1 and RPOT.
- 4) BVR\_WIP : Voltage tapped from wiper arm of RPOT.
- 5) BVR\_A : Voltage tapped from “bottom” of RPOT.

**Note : BVR\_A voltage is left floating on the controller board. To use this circuit, you need to tie this point to a potential (usually GND, available at CNC1 pin 6).**

**CNB1 – Backlight inverter connector: JST B5B-XH-A (Matching type : XHP-5)**

| PIN | SYMBOL  | DESCRIPTION                             |
|-----|---------|---|
| 1   | GND     | Ground                                  |
| 2   | VBKL    | +12V/24VDC, backlight power supply      |
| 3   | BLCTRL  | On/Off control (enable) – see JB2 & JB3 |
| 4   | BVR_WIP | Brightness VR - WIP                     |
| 5   | BVR_A   | Brightness VR A                         |

**CNC1 – OSD switch mount control, Hirose DF13A-12P-1.25H (Mating type : DF13-12S-1.25C)**

| PIN | SYMBOL  | DESCRIPTION   |
|-----|---------|---|
| 1   | PSWIN   | Power button A  |
| 2   | SW_ON   | Power button B  |
| 3   | BVR_A   | Backlight Brightness VR pin A                               |
| 4   | BVR_WIP | Backlight Brightness R pin WIP                              |
| 5   | BVR_B   | Backlight Brightness VR pin B (470 ohm resistor to +5V Vcc) |
| 6   | GND     | Ground  |
| 7   | MENU    | OSD menu  |
| 8   | -/LEFT  | OSD -/Left  |
| 9   | +/RIGHT | OSD +/Right   |
| 10  | SEL_DN  | OSD Select down   |
| 11  | SEL_UP  | OSD Select up   |
| 12  | NC      | No connection   |

The VR for brightness depends on the inverter. The main power load for On/Off is handled by a relay on the controller.

**Example for circuit design :**

- 1.) Choose RPOT = 10K
- 2.) Tie BVR\_A to GND
- 3.) Circuit analysis gives BVR\_WIP as the following (see Figure 1)


$$BVR\_WIP = 5 \times (Rbc/10.47)$$

where BVR\_WIP is in Volts.  
And Rbc is the resistance from the wiper arm to bottom of pot in Kohms.

To evaluate, plug in different values of Rbc :

| Rbc   | BVR_WIP |
|-------|---------|
| 0     | 0 V     |
| 2.5 K | 1.2 V   |
| 5 K   | 2.4 V   |
| 7.5 K | 3.6 V   |
| 10 K  | 4.8 V   |

So this circuit could provide Brightness adjust voltage ranging from 0V to 5V.



---

## TROUBLESHOOTING

### General

A general guide to troubleshooting a flat panel display system it is worth considering the system as separate elements, such as:

- Controller (jumpers, PC settings)
- Panel (controller, cabling, connection, panel, PC settings)
- Backlight (inverter, cabling, backlight tubes)
- Cabling
- Computer system (display settings, operating system)

Through step by step cross checking with instruction manuals and a process of elimination to isolate the problem it is usually possible to clearly identify the problem area.

### No image:

- If the panel backlight is not working it may still be possible to just see some image on the display.
- A lack of image is most likely to be caused by incorrect connection, lack of power, failure to provide a signal or incorrect graphic card settings.

### Image position:

If it is impossible to position the image correctly, i.e. the image adjustment controls will not move the image far enough, then test using another graphics card. This situation can occur with a custom graphics card that is not close to standard timings or if something is in the graphics line that may be affecting the signal such as a signal splitter (please note that normally a signal splitter will not have any adverse effect).

### Image appearance:

- A faulty panel can have blank lines, failed sections, flickering or flashing display
- Incorrect graphics card refresh rate, resolution or interlaced mode will probably cause the image to be the wrong size, to scroll, flicker badly or possibly even no image.
- Incorrect jumper settings on the controller may cause everything from total failure to incorrect image. CAUTION: Do not set the panel power input incorrectly.
- Sparkling on the display: faulty panel signal cable.

### Backlight:

Items to check include: Power input, Controls, Inverter and Tubes generally in this order.

If half the screen is dimmer than the other half:

- Check cabling for the inverter.
- For a specific backlight tube check the AC pins orientation (CAUTION: Never reverse any DC power pins).

Also:

- If adjusting brightness control has no effect the chances are that the VR rating or method of adjusting brightness is not compatible or correctly connected to the inverter.
- If system does not power down when there is a loss of signal

### Continued failure:

If unit after unit keeps failing consider and investigate whether you are short circuiting the equipment or doing something else seriously wrong.

Generally after common sense issues have been resolved we recommend step by step substitution of known working parts to isolate the problem.

The following are some of **LED indicators** onboard that can help to know the health status of the controller board:

#### LED1A

- Green : Valid video signal received on the selected input port.
- Red : No video signal received on the selected input port.
- Off : The board is not powered on.

#### LED5A2

- Green : Panel power is supplied to panel.
- Off : No power is supplied to panel.

#### D1

- Green : V-by-One's signal is detected and locked.
- Off : No V-by-One's signal is detected and locked.

## SPECIFICATIONS

|                              |  |
|------------------------------|--|
| Panel compatibility          | Compatible with 4096x2160 resolutions of TFT LCD panels with V-by-One panel interface.<br><br>A specified BIOS and some factory adjustment is required for individual panel timings. |
| No. of colors                | Up to 3 x 10 bit providing 1.06 billion colors.  |
| Panel power                  | DC 3.3V, 5V, 10V, 12V, 18V   |
| Panel signal                 | V-by-One (8 or 16 Lane)  |
| Video ports                  | DVI-I (Dual Link) in<br>DisplayPort 1.2 in/out (Pass-through)<br>HDMI 1.4 in<br>HDMI 2.0 in  |
| Functions display            | On screen display (OSD) of functions   |
| OSD menu functions           | Image controls:<br>Panel brightness/contrast, Saturation, Hue, Color temperature, Sharpness, Aspect ratio, Rotate, Gamma, PIP/PBP.   |
| OSD menu controls available  | Power On/Off<br>OSD Menu<br>OSD Select up<br>OSD Select down<br>Setting +<br>Setting -   |
| Control interface            | Buttons, RS-232, IR Remote control, Ethernet control   |
| Settings memory              | Settings are stored in non volatile memory   |
| PC Connectivity              | VGA / SVGA / XGA / SXGA / UXGA / WUXGA analog or digital   |
| Controller dimensions        | 203.2mm x 194mm (8" x 7.64")   |
| Power consumption            | 10W approx. (not including panel power consumption)  |
| Power load maximum           | The controller has an overall 3Amp current limit.  |
| Input voltage                | 12V/24VDC +/- 5%   |
| On board battery lifetime    | 3 years at storage (without applying power to the unit). The battery is not rechargeable.  |
| Power protection             | Fuse fitted (Resettable)   |
| DC Power handling            | Reverse power polarity protection is equipped on the board   |
| Storage temperature limits   | -40°C to +70°C   |
| Operating temperature limits | 0°C to +60°C   |

### NOTES

Please note the following:

- For specific panel setup a sample of an LCD may be required (this will be returned) and a copy of the full technical specifications for the panel from the manufacturer.
- Re-layout and custom development services are available.



---

## APPENDIX I – SIGNAL SUPPORT MODE TABLE

### ARGB input port (P1) : (with DVI to VGA adapter)

| Resolution     |
|----------------|
| 640x480 60Hz   |
| 640x480 75Hz   |
| 800x600 56Hz   |
| 800x600 60Hz   |
| 800x600 72Hz   |
| 800x600 75Hz   |
| 1024x768 60Hz  |
| 1024x768 70Hz  |
| 1024x768 75Hz  |
| 1280x768 60Hz  |
| 1280x768 75Hz  |
| 1280x1024 60Hz |
| 1280x1024 75Hz |
| 1360x768 60Hz  |
| 1440x900 60Hz  |
| 1600x900 60Hz  |
| 1600x1200 60Hz |
| 1680x1050 60Hz |
| 1920x1080 60Hz |
| 1920x1200 60Hz |

### DVI input port (P1) :

| Resolution     |
|----------------|
| 640x480 60Hz   |
| 640x480 75Hz   |
| 800x600 56Hz   |
| 800x600 60Hz   |
| 800x600 72Hz   |
| 800x600 75Hz   |
| 1024x768 60Hz  |
| 1024x768 70Hz  |
| 1024x768 75Hz  |
| 1280x768 75Hz  |
| 1280x800 75Hz  |
| 1280x1024 60Hz |
| 1280x1024 75Hz |
| 1360x768 60Hz  |
| 1366x768 60Hz  |
| 1440x900 75Hz  |
| 1600x1200 75Hz |
| 1680x1050 75Hz |
| 1920x1080 60Hz |
| 1920x1200 60Hz |
| 2560x1600 60Hz |
| 3840x2160 30Hz |

**HDMI 1.4 input port (P2 / P3) :**

| <b>Resolution</b> |
|-------------------|
| 640x480 60Hz      |
| 640x480 72Hz      |
| 640x480 75Hz      |
| 800x600 56Hz      |
| 800x600 60Hz      |
| 800x600 72Hz      |
| 800x600 75Hz      |
| 1024x768 60Hz     |
| 1024x768 70Hz     |
| 1024x768 75Hz     |
| 1280x768 60Hz     |
| 1280x768 75Hz     |
| 1280x800 60Hz     |
| 1280x800 75Hz     |
| 1280x1024 60Hz    |
| 1280x1024 75Hz    |
| 1360x768 60Hz     |
| 1366x768 60Hz     |
| 1440x900 75Hz     |
| 1600x1200 75Hz    |
| 1680x1050 75Hz    |
| 1920x1080 60Hz    |
| 1920x1200 60Hz    |
| 2560x1600 60Hz    |
| 3840x2160 30Hz    |

**HDMI 2.0 input port (P4) :**

| <b>Resolution</b> |
|-------------------|
| 640x480 60Hz      |
| 640x480 72Hz      |
| 640x480 75Hz      |
| 800x600 56Hz      |
| 800x600 60Hz      |
| 800x600 72Hz      |
| 800x600 75Hz      |
| 1024x768 60Hz     |
| 1024x768 70Hz     |
| 1024x768 75Hz     |
| 1280x768 60Hz     |
| 1280x768 75Hz     |
| 1280x800 60Hz     |
| 1280x800 75Hz     |
| 1280x1024 60Hz    |
| 1280x1024 75Hz    |
| 1360x768 60Hz     |
| 1366x768 60Hz     |
| 1440x900 75Hz     |
| 1600x1200 75Hz    |
| 1680x1050 75Hz    |
| 1920x1080 60Hz    |
| 1920x1200 60Hz    |
| 2560x1600 60Hz    |
| 3840x2160 30Hz    |
| 3840x2160 60Hz    |
| 4096x2160 60Hz    |

**Display port 1.2 input port (P5) :**

| <b>Resolution</b> |
|-------------------|
| 640x480 60Hz      |
| 640x480 72Hz      |
| 640x480 75Hz      |
| 720x480 60Hz      |
| 720x576 50Hz      |
| 800x600 56Hz      |
| 800x600 60Hz      |
| 800x600 72Hz      |
| 800x600 75Hz      |
| 1024x768 60Hz     |
| 1024x768 70Hz     |
| 1024x768 75Hz     |
| 1280x768 60Hz     |
| 1280x800 60Hz     |
| 1280x1024 60Hz    |
| 1280x1024 75Hz    |
| 1366x768 60Hz     |
| 1400x1050 60Hz    |
| 1440x900 60Hz     |
| 1600x900 60Hz     |
| 1600x1200 60Hz    |
| 1680x1050 60Hz    |
| 1920x1080 60Hz    |
| 1920x1200 60Hz    |
| 2560x1600 60Hz    |
| 3840x2160 30Hz    |
| 3840x2160 60Hz    |
| 4096x2160 60Hz    |

---

## Appendix II – Network connection

The SVX-4096-120 LCD interface controller has an RJ-45 Ethernet port for control and monitoring over a network. This application note introduces the two user interface modes:

- Command line direct mode
- Browser based web server mode

There is also a short overview of the command set and how it is implemented.

### QUICK GUIDE

For experienced users the following quick guide to trying out the network connection and functions may be useful.

**Command line direct mode:** This is relevant when a PC application is used to send and receive commands over the network port.

**Browser based web server mode :** The network port will require an alternative firmware version if the browser based web server mode is required.

- Works with a normal network with DHCP, i.e. must use a router.
- Connect the SVX-4096-120 to the network and ensure power is on.
- Use the IP Locator utility available from the IP-60 web-page.  
<http://www.digitalview.com/media/downloads/IPLocator.zip> (Windows only)
- Double click on the IP address in the IP Locator window, it will open the SVX-4096-120 browser page in your default browser. Alternatively copy the IP address into your browser address line.
- Test the functions that come up on the browser.

For details, please refer to the separate application note.



## Appendix III – RS-232 control protocols and command set

### RS-232 Serial control (Baud rate 2400), 8 bits, 1 stop bit and no parity

*Physical connection :*

Controller side  
 Connector interface : CN8  
 Mating connector : JST XHP-6

Computer side  
 Connector interface : Serial port  
 Mating connector : DB9 Female



| PIN# | Description    |
|------|----------------|
| 4    | RS-232 Tx Data |
| 5    | Ground         |
| 6    | RS-232 Rx Data |

| PIN# | Description    |
|------|----------------|
| 2    | RS-232 Rx Data |
| 3    | RS-232 Tx Data |
| 5    | Ground         |

Remark :

(1) : RS-232 connection cable, 600mm P/N 426090200-3 can be ordered separately for connection.

*Software connection :*

The OSD function can be controlled through sending the RS-232 protocol.

The RS-232 program can be custom-made to fit for application or it can be used the serial control program, like Accessport, Telix or Serial Utility program developed by DigitalView. Please contact your local support for information.

## 1. Commands to implement switch mount control buttons

| Function           | Command | Description                | Remark            |
|--------------------|---------|----------------------------|-------------------|
| Menu button        | 0xf7    | Menu button pressed        | Button equivalent |
| Select-down button | 0xfa    | Select-down button pressed | Button equivalent |
| Select-up button   | 0xfb    | Select-up button pressed   | Button equivalent |
| Right/+ button     | 0xfc    | Right/+ button pressed     | Button equivalent |
| Left/- button      | 0xfd    | Left/- button pressed      | Button equivalent |

## 2. Parameter setting - immediate, relative, reset and query

| Function                            | Command  | Description   | Acknowledge (if enabled)  |
|-------------------------------------|--|---|---|
| Volume control - left+right channel | 0x80, "a"   "A",<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"               | Set audio (L+R) volume =<br>value/increment/decrement<br>Reset<br>Query   | nn = 0x00~ 0x64 (0~100%)<br><br>Default: 0x32 (50%)   |
| Volume control - on/off (mute)      | 0x80, "m"   "M",<br>"0"  <br>"1"  <br>"r"   "R"  <br>"?"                 | Disable audio output.<br>Enable audio output.<br>Reset<br>Query   | "0" - audio off (mute).<br>"1" - audio on. (Default)  |
| Audio selection                     | 0x80, "P" ,<br>"n"<br>"?"<br>"r"   "R"                                   | Select Audio Output<br>Query<br>Reset   | "n" =<br>"0" - P1 (upper left picture) (Default)<br>"1" - P2 (lower left picture)<br>"2" - P3 (upper right picture)<br>"3" - P4 (lower right picture)<br>"A/a" - Analog source<br>Note: P1~P4 audio source is available<br>when video source is either DP or HDMI |
| Brightness control                  | 0x81,<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"<br>"m"<br>"n"            | Set brightness =<br>value/increment/decrement<br>Reset<br>Query<br>Current Source<br>Maximum query<br>Minimum query | nn = 0x00~ 0x64 (0~100%)<br><br>Default: 0x32 (50%)   |
| Contrast control                    | 0x82, "a"   "A",<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"<br>"m"<br>"n" | Set contrast =<br>value/increment/decrement<br>Reset<br>Query<br>Maximum query<br>Minimum query                     | nn = 0x00~ 0x64 (0~100%)<br><br>Default: 0x32 (50%)   |
| Color saturation control            | 0x83,<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"<br>"m"<br>"n"            | Set color saturation =<br>value/increment/decrement<br>Reset<br>Query<br>Maximum query<br>Minimum query             | nn = 0x00~ 0x64 (0~100%)<br><br>Default: 0x32 (50%)   |
| Hue control                         | 0x84,<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"<br>"m"<br>"n"            | Set tint =<br>value/increment/decrement<br>Reset<br>Query<br>Maximum query<br>Minimum query                         | nn = 0x00~ 0x64 (0~100%)<br><br>Default: 0x32 (50%)   |
| Phase control (only for VGA port)   | 0x85,<br>nn   "+"   "-"  <br>"?"   | Set phase =<br>value/increment/decrement<br>Query   | nn = 0x00~ 0x64 (0~100%)  |
| Image H position                    | 0x86,  | Set horizontal position =   | nn = 0x00~ 0x64 (0~100%)  |

Specifications subject to change without notice

|   |   |  |  |
|---|---|--|--|
| (only for VGA port)                     | nn   "+"   "-"  <br>"r"   "R"  <br>"?"                        | value/increment/decrement<br>Reset<br>Query                                  |  |
| Image V position<br>(only for VGA port) | 0x87,<br>nnnn   "+"   "-"  <br>"r"   "R"  <br>"?"             | Set vertical position =<br>value/increment/decrement<br>Reset<br>Query       | nn = 0x00~ 0x64 (0~100%)<br>Default: 0x32 (50%)  |
| Sharpness                               | 0x8a,<br>n   "+"   "-"  <br>"r"   "R"  <br>"?"                | Set sharpness =<br>value/increment/decrement<br>Reset<br>Query               | nn = 0x00~ 0x64 (0~100%)<br>Default: 0x32 (50%)  |
| Clock control (only<br>for VGA port)    | 0x8b,<br>nn   "+"   "-"  <br>"?"                              | Set VGA clock=<br>Value/increment/decrement<br>Query                         | nn = 0x00~ 0x64 (0~100%)   |
| Aspect Ratio                            | 0x8c,<br>"0"   "1"   "9"   "A"  <br>"F"<br>"r"   "R"  <br>"?" | Set video aspect ratio=<br>Value<br>Reset<br>Query                           | "0" – 1:1<br>"1" – fill screen (Default)<br>"9" – 4:3<br>"A" – 16:9<br>"F" – 5:4   |
| Set display<br>orientation              | 0x8e,<br>n  <br>"r"   "R"  <br>"?"                            | Set display orientation =<br>value<br>Reset<br>Query                         | "0" – normal (0 degree) (Default)<br>"1" – vertical flip<br>"2" – horizontal flip<br>"3" – vertical & horizontal flip<br>"4" – rotated 90<br>"5" – rotated 180<br>"6" – rotated 270<br>Note: Rotation is only allowed in 1P mode |
| Rotate OSD                              | 0x8f,<br>"0"  <br>"1"  <br>"3"  <br>"?"                       | Normal OSD rotate<br>rotated 90<br>rotated 270<br>Query                      | "0" – normal OSD. (Default)<br>"1" – rotated 90 OSD.<br>"3" – rotated 270 OSD.   |
| OSD H position                          | 0x90,<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"               | Set OSD horizontal position =<br>value/increment/decrement<br>Reset<br>Query | nn = 0x00~ 0x64 (left ~ right)<br>Default: 0x32 (middle)   |
| OSD V position                          | 0x91,<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"               | Set OSD vertical position =<br>value/increment/decrement<br>Reset<br>Query   | nn = 0x00~ 0x64 (top ~ bottom)<br>Default: 0x32 (middle)   |
| OSD transparency                        | 0x92,<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"               | Set OSD transparency =<br>value/increment/decrement<br>Reset<br>Query        | nn = 0x00~ 0x64 (0~100%)<br>Default: 0x00 (No transparency)  |
| OSD menu timeout                        | 0x93,<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"               | Select menu timeout =<br>value/increment/decrement<br>Reset<br>Query         | OSD menu timeout value.<br>nn = 0x0A – Always on<br>nn = 0x0B - 0x3C (11~60sec)<br>Default: 0x0B (11sec)   |
| Input main video<br>(P1) select         | 0x98,<br>nn   "+"   "-"  <br>"r"   "R"  <br>"?"               | Select P1 video input =<br>value/next input/previous input<br>Reset<br>Query | "nn" =<br>"0x41,0x31" A0: VGA<br>"0x50, 0x31" D0: DP (Default)<br>"0x48,0x31" D1: HDMI<br>"0x48,0x32" D2: HDMI<br>"0x48,0x33" D3: HDMI<br>"0x46,0x31" D4: DVI  |
| Auto source seek                        | 0x99,<br>"0"   "1"  <br>"r"   "R"                             | Set auto source seek =<br>Disable/Enable<br>Reset                            | Default: "1" (Enable)  |



|                                 |   |   |  |
|---------------------------------|---|---|--|
|                                 | “?”   | Query   |  |
| Source Layout                   | 0x9a,<br>n  <br>“I”   “R”  <br>“?”              | Select video source layout =<br>Single, PIP, PBP, 4P<br>Reset,<br>Query     | “n” :<br>“0”- 1P (Single) (Default)<br>“1”- 2P PIP<br>“2”- 2P PBP (Left Right)<br>“3”- 2P PBP (Top Bottom)<br>“4”- 4P  |
| GAMMA value select              | 0x9d,<br>n  <br>“I”   “R”<br>“?”                | Select GAMMA value =<br>Value<br>Reset<br>Query                             | “n”:<br>“5” – 1.8,<br>“7” – 2.0,<br>“2” – 2.2, (Default)<br>“A” – 2.4  |
| Auto power off                  | 0x9f,<br>“0”   “1”  <br>“I”   “R”  <br>“?”      | Set auto power save option =<br>Disable/Enable<br>Reset<br>Query            | “n”:<br>“0” – Disable auto power off<br>“1” – Enable auto power off (Default)  |
| Hot key 1 (plus and minus keys) | 0xa0, “1”,<br>n  <br>“I”   “R”  <br>“?”         | Set Hot key 1=<br>Value<br>Reset<br>Query                                   | “n”:<br>“1” – volume<br>“2” – brightness<br>“3” – contrast<br>“4” – color saturation<br>“5” – input source (P1 source)<br>“9” – PIP size<br>“B” – No hot key function (Default)<br>“D” – PIP Swap<br>“E” – Aspect ratio<br>“G” – Hue<br>“H” – Backlight level<br>“I” – VGA Auto picture adjust<br>“L” - Sharpness<br>“M” - Display mode (select 1P, 2P PIP,<br>2P PBP or 4P) |
| Hot key 2 (up and down keys)    | 0xa0, “2”,<br>n  <br>“I”   “R”  <br>“?”         | Set Hot key 2=<br>Value<br>Reset<br>Query                                   | “n”:<br>“1” – volume<br>“2” – brightness<br>“3” – contrast<br>“4” – color saturation<br>“5” – input source (P1 source)<br>“9” – PIP size<br>“B” – No hot key function (Default)<br>“D” – PIP Swap<br>“E” – Aspect ratio<br>“G” – Hue<br>“H” – Backlight level<br>“I” – VGA Auto picture adjust<br>“L” - Sharpness<br>“M” - Display mode (select 1P, 2P PIP,<br>2P PBP or 4P) |
| Runtime counter                 | 0xa1,<br>nnnnn  <br>“I”   “R”  <br>“?”          | Set runtime counter value =<br>nnnnn (* 0.5 hour)<br>Reset to zero<br>Query | Runtime = nnnnn.<br>Max. input = 0x1ffe (0x1ffe * 0.5 hour<br>= 65535 hours)<br>Runtime counter counts when backlight is<br>on   |
| PIP H position                  | 0xa4,<br>nn   “+”   “-”  <br>“I”   “R”  <br>“?” | Set PIP horizontal position=<br>value/go right/go left<br>Reset<br>Query    | PIP window horizontal position.<br>nn: 0x00(left)~0x64(right)<br>Default: 0x64   |
| PIP V position                  | 0xa5,<br>nn   “+”   “-”  <br>“I”   “R”  <br>“?” | Set PIP vertical position=<br>value/go down/go up<br>Reset<br>Query         | PIP window vertical position.<br>nn: 0x00(top)~0x64(bottom)<br>Default: 0x64   |

|                                      |  |  |  |
|--------------------------------------|--|--|--|
| PIP window size select               | 0xa6,<br>nn  <br>“r”   “R”  <br>“?”                        | Select PIP window size =<br>PIP window size value<br>Reset<br>Query  | nn:<br>0x00(smallest)~0x0A (largest)<br>Default: 0x0A  |
| PIP /P2 source select                | 0xa7,<br>nn  <br>“r”   “R”  <br>“?”                        | Select PIP or P2 video source =<br>Video source value<br>Reset<br>Query  | P2 is:<br>2P PBP left right: right window<br>2P PBP top bottom: bottom window<br>4P: lower left window<br><br>“nn” =<br>“0x41,0x31” A0: VGA<br>“0x50,0x31” D0: DP<br>“0x48,0x31” D1: HDMI (Default)<br>“0x48,0x32” D2: HDMI<br>“0x48,0x33” D3: HDMI<br>“0x46,0x31” D4: DVI<br><br>Please note that PIP or PBP mode should be enabled first before select video source. |
| P3 source select                     | 0xa7, “c”<br>nn  <br>“r”   “R”  <br>“?”                    | Select P3 video source =<br>Video source value<br>Reset<br>Query   | P3 is upper right window in 4P mode<br><br>“nn” =<br>“0x41,0x31” A0: VGA<br>“0x50,0x31” D0: DP<br>“0x48,0x31” D1: HDMI<br>“0x48,0x32” D2: HDMI (Default)<br>“0x48,0x33” D3: HDMI<br>“0x46,0x31” D4: DVI<br><br>Please note that 4P PBP mode should be enabled first before select video source.  |
| P4 source select                     | 0xa7, “d”<br>nn  <br>“r”   “R”  <br>“?”                    | Select P4 video source =<br>Video source value<br>Reset<br>Query   | P4 is lower right window in 4P mode<br><br>“nn” =<br>“0x41,0x31” A0: VGA<br>“0x50,0x31” D0: DP<br>“0x48,0x31” D1: HDMI<br>“0x48,0x32” D2: HDMI<br>“0x48,0x33” D3: HDMI (Default)<br>“0x46,0x31” D4: DVI<br><br>Please note that 4P PBP mode should be enabled first before select video source.  |
| Colour temperature select            | 0xb3,<br>n  <br>“r”   “R”  <br>“?”                         | Select colour temperature =<br>value<br>Reset<br>Query   | “n” =<br>“2” – 6500K. (Default)<br>“4” – User<br>“5” – 9300K<br>“6” – 7500K<br>“7” – 5800K<br>“8” – sRGB<br>“9” – 3200K<br>“A” – 2600K   |
| Red level of User colour temperature | 0xb4,<br><br>nn   “+”   “-”  <br>“r”   “R”  <br>“?”<br>“m” | Set the level of the red channel for the user colour temp. =<br>value/increment/decrement<br>Reset<br>Query<br>Maximum query | nn: 0x00~ 0xff (0~255)<br><br>Default: 0x80  |

|  |   |  |   |
|--|---|--|---|
|  | “n”   | Minimum query  |   |
| Green level of User colour temperature | 0xb5,<br>nn   “+”   “-”  <br>“r”   “R”  <br>“?”<br>“m”<br>“n” | Set the level of the green channel for the user colour temp. = value/increment/decrement<br>Reset<br>Query<br>Maximum query<br>Minimum query | nn: 0x00~ 0xff (0~255)<br><br>Default: 0x80   |
| Blue level of User colour temperature  | 0xb6,<br>nn   “+”   “-”  <br>“r”   “R”  <br>“?”<br>“m”<br>“n” | Set the level of the blue channel for the user colour temp. = value/increment/decrement<br>Reset<br>Query<br>Maximum query<br>Minimum query  | nn: 0x00~ 0xff (0~255)<br><br>Default: 0x80   |
| Video horizontal resolution enquiry    | 0xb7  | Horizontal resolution (in pixels) in 3 to 4 digit hex number   |   |
| Video vertical resolution enquiry      | 0xb8  | Vertical resolution (in lines) in 3 digit hex number   |   |
| Video horizontal sync frequency        | 0xb9  | Horizontal sync frequency (in units of 100Hz) in 3 digit hex number  |   |
| Video vertical sync frequency          | 0xba  | Vertical sync frequency (in units of Hz) in 3 digit hex number and 1 char  | “nnnc” = vertical frequency<br>nnn = 3 digit hex<br>c= “i” (interlace) or “p” (progressive)                         |
| OSD status enquiry                     | 0xbb  | Status of OSD  | “0” – OSD turned off<br>“1” – OSD turned on   |
| Display video information box          | 0xbc,<br>“?”  <br>“0”  <br>“1”                                | Query<br>No video info box shown<br>After switching to a new video source, the video info box is displayed for 5 seconds.                    | “0” – disabled.<br>“1” – enabled. (Default)   |
| OSD turn off                           | 0xbd  | Turn off the OSD.  | “0” – fail.<br>“1” – successful.  |
| MEMC control                           | 0xca, “9”,<br>“0”   “1”  <br>“?”                              | Disable/Enable MEMC<br>Query   | “0” – disabled<br>“1” – enabled<br>Default state is depended on SW1 DIP switch setting.                             |
| Backlight control                      | 0xe0,<br>nn   “+”   “-”  <br>“R”   “r”  <br>“?”               | Set Backlight level = value/increment/decrement<br>Reset<br>Query  | nn = 0x00~ 0x64 (0~100%)<br><br>Default: 0x64 (100%)  |
| Backlight On/Off                       | 0xe1,<br>“0”   “1”  <br>“R”   “r”<br>“?”                      | Backlight Off / Backlight On<br>Reset<br>Query   | “0” – Backlight Off<br>“1” – Backlight On. (Default)  |
| Swap PIP / 2P PBP video source         | 0xe3  | Swap Main and PIP Source (PIP mode), left & right source (PBP LR) or Top & Bottom (PBP TB)   | “0” – fail.<br>“1” – successful.  |
| Backlight DA/PWM                       | 0xe5<br>“0”   “1”  <br>“R”   “r”<br>“?”                       | Set backlight control method:<br>PWM / DA<br>Reset<br>Query  | “0” – PWM (Default)<br>“1” – D/A  |
| Backlight PWM frequency                | 0xe6,<br>nnn   “+”   “-”  <br>“R”   “r”  <br>“?”              | Set backlight PWM frequency = value/increase 20Hz/decrease 20Hz<br>Reset<br>Query  | Value<br>100Hz : “0”, “6”, “4”<br>120Hz : “0”, “7”, “8”<br>140Hz : “0”, “8”, “C”<br>160Hz : “0”, “A”, “0” (Default) |

|                               |  |  |  |
|-------------------------------|--|--|--|
|                               |  |  | 180Hz : "0","B","4"<br>200Hz : "0","C","8"<br>220Hz : "0","D","C"<br>240Hz : "0","F","0"<br>260Hz : "1","0","4"<br>280Hz : "1","1","8"<br>300Hz : "1","2","C"<br>320Hz : "1","4","0"<br>340Hz : "1","5","4"<br>360Hz : "1","6","8"<br>380Hz : "1","7","C"<br>400Hz : "1","9","0"<br>420Hz : "1","A","4"<br>440Hz : "1","B","8" |
| Backlight Invert              | 0xe7<br>"0"   "1"  <br>"R"   "r"<br>"?"                                      | Set invert backlight level :<br>Off / On<br><br>Reset<br>Query                               | "0" – Off (Default)<br>"1" – On  |
| PIP window transparency Level | 0xed,<br>nn   "+"   "-"  <br>"R"   "r"  <br>"?"                              | Select PIP transparency level =<br>value/increase/decrease<br>Reset<br>Query                 | nn:<br>0x00~0x0A (no ~ total transparency)<br>Default: 0x00  |
| Minimum backlight level       | 0xee, "0x5C"<br>nn   "+"   "-"  <br>"R"   "r"  <br>"?"                       | Set minimum backlight level=<br>value/increment/decrement<br>Reset<br>Query                  | Minimum Backlight value.<br>nn: 0x00 ~ 0x32 (0~50%)<br>Default: 5%   |
| OSD switch mount Lock         | "0xee", "0x62"<br>"0"   "1"<br>"?"   | Unlock / Lock<br>Query   | "0"- Unlock (Default)<br>"1"- Lock, no response to OSD switch mount keys   |
| Default Power                 | "0xee", "0x6B",<br>"0x50"<br>"0" <br>"1" <br>"?"                             | Default power state after supplying power to controller<br>Off<br>On<br>Query                | "0" - default power off<br>"1" - default power on  |
| Color Effect                  | "0xee", "0x71",<br>"0x30"<br>"0" "1" "2" "3" "4"<br> "5"<br>"?"<br>"r"   "R" | Select Color Effect<br><br>Value<br><br>Query<br>Reset                                       | "0" = Standard (Default)<br>"1" = Game<br>"2" = Movie<br>"3" = Photo<br>"4" = Vivid<br>"5" = User  |
| Vby1 pin setting              | "0xee", "0x73",<br>0x30 0x31 ... 0x39,<br><br>"0"   "1"                      | Set Vby1 pin state<br>Pin no.: 0x30=pin15,<br>0x31=pin16,...., 0x39=pin24<br>Pin logic level | "0" = set to low (Default)<br>"1" = set to high  |
|                               |  |  |  |

### 3. Other control

| Function                  | Command                     | Description  | Acknowledge (if enabled)   |
|---------------------------|-----------------------------|--|--|
| Select RS-232 acknowledge | 0xc1, "0"   "1"             | Disable/enable command acknowledge.  | "0" – acknowledge disabled.<br>"1" – acknowledge enabled. (Default)  |
| VGA auto adjust           | 0xc3                        | Start VGA auto adjust  | "0" – fail.<br>"1" – successful.   |
| Command availability      | 0xc4, nn / nnnn             | Check whether a command is available.  | "0" – not available.<br>"1" – available.<br><br>e.g "0x81" command<br>send<br>"0xc4 0x38 0x31"<br>feedback<br>"0xc4 0x38 0x31 0x31"<br><br>e.g "0xee 0x5c" command<br>send<br>"0xc4 0x45 0x45 0x35 0x43"<br>feedback<br>"0xc4 0x45 0x45 0x35 0x43 0x31"                                  |
| VGA auto color gain       | 0xc5                        | Start VGA auto-calibration of gain of the RGB amplifier.   | "0" – fail.<br>"1" – successful.   |
| Power On/Off              | 0xc8,<br>"0"   "1"  <br>"?" | Soft power on/off<br>off/on<br>query   | "0" – soft power off.<br>"1" – soft power on.  |
| Query video input status  | 0xc9                        | Query the status of the displaying video windows source  | Input status nn nn:<br>"0", "0" : no video source / disabled<br>"A", "1" A0: VGA<br>"F", "1" D4: DVI<br>"H", "1" D1: HDMI<br>"H", "2" D2: HDMI<br>"H", "2" D3: HDMI<br>"P", "1" D0: DP<br><br>Feedback 4 video windows status in form of:<br>nn nn, nn nn, nn nn, nn nn (P1, P2, P3, P4) |
| Query BIOS version        | 0xcb, "0"                   | Read BIOS version  | BIOS version "VV.YY.ZZ"<br>VV = Vx or Ex, (x is version digit)<br>V = Release version<br>E = Engineering Sample<br><br>YY= Version Number<br><br>ZZ= Customer Number   |
| Query PCBA number         | 0xcb, "1"                   | Read PCBA number   | "nnnnn" = PCBA number<br>SVX-4096-120= "41759"   |
| Query Revision Number     | 0xcb, "3"                   | Read Revision Number   | "nn" = Revision number AA in firmware version no. "VV.YY.ZZ.AA"  |
| Reset parameters          | 0xce                        | Reset all parameters to default value  | "1" – successful.  |
| Reset all parameters      | 0xcf                        | Reset all parameters, including user color temperature setting, for all video modes to default value | "1" - successful.  |

n = 1-byte ascii-coded hex number, e.g., parameter value of 0x1 is represented by “1” (0x31).  
 mn or nn = 2-byte ascii-coded hex number, e.g., parameter value of 0x1e is represented by “1”, “e” | “E” (0x31, 0x6e|0x4e).

The RS-232 command strings sent in one time can support up to 380 bytes via CN8 port  
 The RS-232 command string sent in one time can support up to 50 bytes via CN1 or J1 port.

n = 1-byte ascii-coded hex number, e.g., parameter value of 0x1 is represented by “1” (0x31).  
 mn or nn = 2-byte ascii-coded hex number, e.g., parameter value of 0x1e is represented by “1”, “e” | “E” (0x31, 0x6e|0x4e).


Please refer to the ASCII to Hex convert table below.

### Hex to ASCII conversion table


| Hex  | ASCII | Hex  | ASCII | Hex  | ASCII | Hex  | ASCII |
|------|-------|------|-------|------|-------|------|-------|
| 0x30 | 0     | 0x41 | A     | 0x61 | a     | 0x2B | +     |
| 0x31 | 1     | 0x42 | B     | 0x62 | b     | 0x2D | -     |
| 0x32 | 2     | 0x43 | C     | 0x63 | c     | 0x3F | ?     |
| 0x33 | 3     | 0x44 | D     | 0x64 | d     |      |       |
| 0x34 | 4     | 0x45 | E     | 0x65 | e     |      |       |
| 0x35 | 5     | 0x46 | F     | 0x66 | f     |      |       |
| 0x36 | 6     | 0x47 | G     | 0x67 | g     |      |       |
| 0x37 | 7     | 0x48 | H     | 0x68 | h     |      |       |
| 0x38 | 8     | 0x49 | I     | 0x69 | i     |      |       |
| 0x39 | 9     | 0x4A | J     | 0x6A | j     |      |       |
|      |       | 0x4B | K     | 0x6B | k     |      |       |
|      |       | 0x4C | L     | 0x6C | l     |      |       |
|      |       | 0x4D | M     | 0x6D | m     |      |       |
|      |       | 0x4E | N     | 0x6E | n     |      |       |
|      |       | 0x4F | O     | 0x6F | o     |      |       |
|      |       | 0x50 | P     | 0x70 | p     |      |       |
|      |       | 0x51 | Q     | 0x71 | q     |      |       |
|      |       | 0x52 | R     | 0x72 | r     |      |       |
|      |       | 0x53 | S     | 0x73 | s     |      |       |
|      |       | 0x54 | T     | 0x74 | t     |      |       |
|      |       | 0x55 | U     | 0x75 | u     |      |       |
|      |       | 0x56 | V     | 0x76 | v     |      |       |
|      |       | 0x57 | W     | 0x77 | w     |      |       |
|      |       | 0x58 | X     | 0x78 | x     |      |       |
|      |       | 0x59 | Y     | 0x79 | y     |      |       |
|      |       | 0x5A | Z     | 0x7A | z     |      |       |

## Appendix IV – Mapping definition


Definition of division




1 Division  
(Non-Division)



2 Division




4 Division




8 Division

# Input data mapping


VESA Format (LVDS)  
(Mapping A)



VESA Format (LVDS)  
(Mapping B)



JEIDA Format (LVDS)





## Appendix V – DV remote control unit work for SVX-4096-120


**P/N 559000106-3 :**  
DigitalView remote control unit  
(without DV logo silk screen  
printing)

**P/N 559000105-3 :**  
DigitalView remote control unit  
(with DigitalView logo silk screen  
printing)



| BUTTON                  | FUNCTION   |
|-------------------------|--|
| POWER BUTTON            | Soft power ON/OFF button.  |
| SEL UP (▲) / SEL DN (▼) | 1. In OSD menu, pressing "SEL UP" button to move previous level of selection.<br>2. In OSD menu, pressing "SEL DN" button to move next level of selection or to CONFIRM the selection. |
| + BUTTON                | 1. When OSD menu displayed, press this button to select functions (forward) or increase the values.  |
| - BUTTON                | 1. When OSD menu displayed, press this button to select functions (backward) or decrease the values.   |
| AV/TV                   | 1. Show input source selection menu.   |
| OSD NEXT BUTTON         | 1. Use to turn on/off the OSD menu.  |
| Mute                    | 1. Mute / Un-mute audio (if external audio board is connected)   |
| PIP                     | 1. Toggle between PIP mode and 1P mode.  |

\* Sequence of Input source selection (Press "+" Button to change source, Press "SEL DN" to confirm)



---

**Appendix VI – PIP mix table**

| PIP \ MAIN       | DVI (P1/CN2) | HDMI (P2/CN16) | HDMI (P3/CN5) | HDMI (P4) | DisplayPort (P5) |
|------------------|--------------|----------------|---------------|-----------|------------------|
| DVI (P1/CN2)     | Yes          | Yes            | Yes           | Yes       | Yes              |
| HDMI (P2/CN16)   | Yes          | Yes            | Yes           | Yes       | Yes              |
| HDMI (P3/CN5)    | Yes          | Yes            | Yes           | Yes       | Yes              |
| HDMI (P4)        | Yes          | Yes            | Yes           | Yes       | Yes              |
| DisplayPort (P5) | Yes          | Yes            | Yes           | Yes       | Yes              |

---

## WARRANTY

The products are warranted against defects in workmanship and material for a period of three (3) year from the date of purchase provided no modifications are made to it and it is operated under normal conditions and in compliance with the instruction manual.

The warranty does not apply to:

- Product that has been installed incorrectly, this specifically includes but is not limited to cases where electrical short circuit is caused.
- Product that has been altered or repaired except by the manufacturer (or with the manufacturer's consent).
- Product that has subjected to misuse, accidents, abuse, negligence or unusual stress whether physical or electrical.
- Ordinary wear and tear.

Except for the above express warranties, the manufacturer disclaims all warranties on products furnished hereunder, including all implied warranties of merchantability and fitness for a particular application or purpose. The stated express warranties are in lieu of all obligations or liabilities on the part of the manufacturer for damages, including but not limited to special, indirect consequential damages arising out of or in connection with the use of or performance of the products.

---

## CAUTION

Whilst care has been taken to provide as much detail as possible for use of this product it cannot be relied upon as an exhaustive source of information. This product is for use by suitably qualified persons who understand the nature of the work they are doing and are able to take suitable precautions and design and produce a product that is safe and meets regulatory requirements.

---

## LIMITATION OF LIABILITY

The manufacturer's liability for damages to customer or others resulting from the use of any product supplied hereunder shall in no event exceed the purchase price of said product.

---

## TRADEMARKS

The following are trademarks of Digital View Ltd:

- Digital View
- SVX-4096-120

---

## CONTACT DETAILS

Digital View has offices in Asia, Europe and USA :

### USA

Digital View Inc.  
18440 Technology Drive  
Building 130  
Morgan Hill,  
California, 95037  
USA

**Tel:** (1) 408-782 7773      **Fax:** (1) 408-782 7883

**Sales:** [ussales@digitalview.com](mailto:ussales@digitalview.com)

### EUROPE

Digital View Ltd.  
The Lake House  
Knebworth Park  
Herts, SG3 6PY  
UK

**Tel:** +44-(0)20-7631-2150      **Fax:** +44-(0)20-7631-2156

**Sales:** [uksales@digitalview.com](mailto:uksales@digitalview.com)

### ASIA

Digital View Ltd  
705-708, 7/F Texwood Plaza  
6 How Ming St.  
Kwun Tong  
Hong Kong

**Tel:** (852) 2861 3615      **Fax:** (852) 2520 2987

**Sales:** [hksales@digitalview.com](mailto:hksales@digitalview.com)

### WEBSITE

[www.digitalview.com](http://www.digitalview.com)

## Revision History

| Date             | Rev No. | Page | Summary       |
|------------------|---------|------|---------------|
| December 6, 2016 | 1.0     | All  | First issued. |
|                  |         |      |               |